



Pushing Performance



People | Power | Partnership

HARTING

M8 / M12 Circular Connectors

Transforming customer wishes into concrete solutions



The HARTING Technology Group is skilled in the fields of electrical, electronic and optical connection, transmission and networking, as well as in manufacturing, mechatronics and software creation. The Group uses these skills to develop customized solutions and products such as connectors for energy and data transmission applications including, for example, mechanical engineering, rail technology, wind energy plants, factory automation and the telecommunications sector. In addition, HARTING also produces electro-magnetic components for the automobile industry and offers solutions in the field of Enclosures and Shop Systems.

The HARTING Group currently comprises 37 subsidiary companies and worldwide distributors employing a total of more than 3.800 staff.



HARTING Subsidiary company



HARTING Representatives

We aspire to top performance.

Connectors ensure functionality. As core elements of electrical and optical wiring, connection and infrastructure technologies, they are essential in enabling the modular construction of devices, machines and systems across a very wide range of industrial applications. Their reliability is a crucial factor guaranteeing smooth functioning in the manufacturing area, in telecommunications, applications in medical technology – in fact, connectors are at work in virtually every conceivable application area. Thanks to the consistent further development of our technologies, customers enjoy investment security and benefit from durable, long term functionality.

Always at hand, wherever our customers may be.

Increasing industrialization is creating growing markets characterized by widely diverging demands and requirements. The search for perfection, increasingly efficient processes and reliable technologies is a common factor in all sectors across the globe.

HARTING is providing these technologies – in Europe, America and Asia. The HARTING professionals at our international subsidiaries engage in close, partnership based interaction with our customers, right from the very early product development phases, in order to realize customer demands and requirements in the best possible manner.

Our people on location form the interface to the centrally coordinated development and production departments. In this way, our customers can rely on consistently high, superior product quality – worldwide.

Our claim: Pushing Performance.

HARTING provides more than optimally attuned components. In order to serve our customers with the best possible solutions, HARTING is able to contribute a great deal more and play a closely integrative role in the value creation process.

From ready assembled cables through to control racks or ready-to-go control desks: Our aim is to generate the maximum benefits for our customers – without compromise!

Quality creates reliability – and warrants trust.

The HARTING brand stands for superior quality and reliability – worldwide. The standards we set are the result of consistent, stringent quality management that is subject to regular certifications and audits.

EN ISO 9001, the EU Eco-Audit and ISO 14001:2004 are key elements here. We take a proactive stance to new requirements, which is why HARTING ranks among the first companies worldwide to have obtained the new IRIS quality certificate for rail vehicles.



HARTING technology creates added value for customers.

Technologies by HARTING are at work worldwide. HARTING's presence stands for smoothly functioning systems, powered by intelligent connectors, smart infrastructure solutions and mature network systems. In the course of many years of close, trust-based cooperation with its customers, the HARTING Technology Group has advanced to one of the worldwide leading specialists for connector technology. Extending beyond the basic functionalities demanded, we offer individual customers specific and innovative solutions. These tailored solutions deliver sustained effects, provide investment security and enable customers to achieve strong added value.

Opting for HARTING opens up an innovative, complex world of concepts and ideas.

In order to develop connectivity and network solutions serving an exceptionally wide range of connector applications and task scopes in a professional and cost optimized manner, HARTING not only commands the full array of conventional tools and basic technologies. Over and beyond these capabilities, HARTING is constantly harnessing and refining its broad base of knowledge and experience to create new solutions that ensure continuity at the same time. In securing this know-how lead, HARTING draws on a wealth of sources from both in-house research and the world of applications alike.

Salient examples of these sources of innovative knowledge include microstructure technologies, 3D design and construction technology, as well as high temperature

or ultrahigh frequency applications that are finding use in telecommunications or automation networks, in the automotive industry, or in industrial sensor and actuator applications, RFID and wireless technologies, in addition to packaging and housing made of plastics, aluminum or stainless steel.

HARTING solutions extend across technology boundaries.

Drawing on the comprehensive resources of the group's technology pool, HARTING devises practical solutions for its customers. Whether this involves industrial networks for manufacturing automation, or hybrid interface solutions for wireless telecommunication infrastructures, 3D circuit carriers with microstructures, or cable assemblies for high-temperature applications in the automotive industry - HARTING technologies offer far more than components, and represent mature, comprehensive solutions attuned to individual customer requirements and wishes. The range covers ready-to-use cable configurations, completely assembled backplanes and board system carriers, as well as fully wired and tested control panels.


In order to ensure the future proof design of RF- and EMC-compatible interface solutions, the central HARTING laboratory (certified to EN 45001) provides simulation tools, as well as experimental, testing and diagnostics facilities all the way through to scanning electron microscopes. In the selection of materials and processes, lifecycle and environmental aspects play a key role, in addition to product and process capability considerations.



HARTING knowledge is practical know-how generating synergy effects.

HARTING commands decades of experience with regard to the applications conditions of connectors in telecommunications, computer and network technologies and medical technologies, as well as industrial automation technologies, such as the mechanical engineering and plant engineering areas, in addition to the power generation industry or the transportation sector. HARTING is highly conversant with the specific application areas in all of these technology fields.

The key focus is on applications in every solution approach. In this context, uncompromising, superior quality is our hallmark. Every new solution found will invariably flow back into the HARTING technology pool, thereby enriching our resources. And every new solution we go on to create will draw on this wealth of resources in order to optimize each and every individual solution. In this way, HARTING is synergy in action.



The **HARTING eCatalogue** is an electronic catalogue with a part configuration and 3D components library.

Here you can choose a connector according to your requirements. Afterwards you are able to send your inquiry directly to a HARTING sales partner.

The drawings to every single part are available in PDF-format.


The parts are downloadable in 2D-format (DXF) and 3D-format (IGES, STEP).

The 3D-models can be viewed with a VRML-viewer.


You can find the **HARTING eCatalogue** at www.HARTING.com.




Product overview



Product selection



Product configuration



Product combination

Product samples: Fast-track delivery to your desk, free of charge

The new free express sample service in the HARTING eCatalogue allows customers to order samples immediately, easily and completely free of charge. A broad selection from the device connectivity product portfolio is now available. If a product is unavailable, the system offers alternative products with similar features that can be requested at a mouse click.

The free samples are shipped within 24 hours at no cost to you. This service enables tremendous flexibility, especially in the design phase of projects.


General information

It is the customer's responsibility to check whether the components illustrated in this catalogue also comply with different regulations from those stated in special fields of applications.

We reserve the right to modify designs or substance of content in order to improve quality, keep pace with technological advancement or meet particular requirements in production.

No part of this catalogue may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed by means of electronic systems without the prior written consent of HARTING Electronics GmbH, Espelkamp. We are bound by the German version only.

Directory	Chapter	
General information	01	01
M8	02	02
M12	03	03
<i>har-speed</i> M12 data connectors	04	04
7/8" HARAX®	05	05
HARAX® panel feed-through	06	06
INOX – Solutions for extreme demands	07	07
List of part numbers	Be	Be
Addresses		



Directory	Page
1. General information	01
1.1 Circular connectors	01.02
1.2 Special series features	01.03
1.3 Termination expertise	01.04
1.4 Specifications, approvals, mating faces and pin assignments	01.05

01

Standardized circular connectors with M8, M12 and 7/8" thread are in widespread use in the installation of machines and systems. HARTING offers a portfolio of field-assembly angled and straight M8, M12 and 7/8" connectors which are attuned to meet all relevant automation requirements. The housings are available as plastic and as metal variant. In addition to the standard circular connectors for sensors/actuators, HARTING is offering standardized circular connectors such as the M12 variants to meet the special requirements of communication technology (Ethernet, Ethernet/IP, PROFINET, Profibus, Devicenet and CAN).

The HARTING product range comprises connectors, ready-to-use patch cables and corresponding accessories. The easy-to-handle *HARAX®* quick connection technology is available for the in situ assembly of M8 and M12 connectors and

does not require the use of special tools. The portfolio of circular connectors is rounded off by the *har-speed* M12 connector family. The *har-speed* connectors are optimized for machinery and system applications with high bandwidth as well as for the IP67 infrastructure. HARTING's comprehensive and user-friendly circular connector range enables cost-effective and quick realization of all wiring and communication tasks in automation projects.

APPLIANCE INTEGRATION:

In order to support the implementation of appliances with degree of protection IP65 / IP67, HARTING offers panel feed-through devices with ready-to-use patch cables and female contact modules for direct mounting on PCBs.



01
02

QUICK CONNECTION WITH HARAX®:

The HARTING HARAX® quick connection technology is an ideal solution for the in situ assembly of M8/M12 connectors. Users only have to strip the cable insulation, insert the conductors, and screw the connector together in order to produce a gas-proof and vibration resistant connection. HARAX® is a universal technology deployed in diverse connector series to wire data, signal and power lines and represents the current standard connection for Fieldbus and Fast Ethernet.



ASSEMBLED SYSTEM CABLES:

HARTING offers a comprehensive range of ready-to-use M8/M12 system cables for the quick wiring of sensors and actuators. HARTING also offers ready-to-use and tested system cables for special Ethernet communication such as PROFINET and Ethernet/IP. HARTING also provides custom patch cables which are also available as overmoulded versions. The range of solutions comprises shielded and non-shielded cables with diverse structures, as required in drag chain applications, for example.



M12 FEMALE SOCKETS FOR PCB MOUNTING:

Straight and angled contact inserts are available for direct soldering on PCBs. HARTING has developed special shielded contact inserts category 5 to ISO/IEC 11801 for Ethernet technology which meet the stringent requirements for railway applications.






WIRE TERMINATION EXPERTISE


1. IDC INSULATION DISPLACEMENT TERMINALS

IDC (insulation displacement contact) technology facilitates the simple and safe termination of solid and flexible conductors. With IDC technology, a blade cuts through the wire insulation and produces an elastic termination in a single pass. This gas-proof connection provides maximum safety even for the lowest currents and voltages. HARAX® Fast termination technology is a special feature offered by HARTING which combines the insulation displacement connector with a wire guide element for conveniently producing on-site field installation without special tools. Technical requirements for IDC technology are standardized in IEC 60 352-3.



2. CRIMP TERMINALS

Gas-proof and the miniaturized contact technology are synonymous with crimp technology. The flexible conductor is inserted into the crimp contact and is retained by controlled deformation. This technology is similar to a cold welding process and provides maximum aging resistance and mechanical resistance to shock and vibration. Crimp machines facilitate the efficient, streamlined production of system cable assemblies, and crimp technology can also be deployed for field assemblies using the corresponding hand crimp tools. The technical requirements for crimp technology are standardized in IEC 60 352-2.




PCB TERMINATION EXPERTISE

7. THT SOLDERING TECHNOLOGY

Proven over decades, standard soldering technologies deliver maximum stability and process reliability.


The soldering pins of the connectors are inserted into the through-plated PCB holes and can then be soldered simultaneously with other components in a wave soldering process.



8. SMC SOLDERING TECHNOLOGY

The connector is inserted into through-plated PCB holes similar to standard component assembly for processing with SMC (Surface Mount Compatible) soldering technology. Insertion of these SMT components can be automated by means of Pick & Place assembly in preparation for a reflow soldering process together with the surface-mounted component.

This connection technology is characterized by high mechanical strength and is facilitated by a design that is specially adapted to the reflow soldering process (high-temperature materials).



9. SMT SOLDERING TECHNOLOGY

By contrast to through-plated assembly, the SMT (Surface Mounted Technology) connectors are soldered directly onto the PCB surface by means of soldering pads.

This process represents a uniform connection technology for PCB assembly and offers the advantage of SMT connectors that do not require separate wave soldering.


Specifications

IEC 60 352-4, IEC 61076-2-104, IEC 61076-2-101, IEC 61076-2-109,




01


M8 circular connectors, mating face acc. to IEC 61076-2-104




Male, 3 poles



Male, 4 poles




Female, 3 poles




Female, 4 poles

M12 circular connectors, mating face acc. to IEC 61076-2-101


A-coding




Male, 4 poles




Male, 5 poles




Male, 8 poles



Female, 4 poles




Female, 5 poles




Female, 8 poles

B-coding




Male, 5 poles




Female, 5 poles

D-coding




Male, 4 poles




Female, 4 poles

X-coding, mating face acc. to IEC 61076-2-109




Male, 8 poles




Female, 8 poles

7/8"



Male, 5 poles



Female, 5 poles

Pin assignment



X-coding, mating face acc. to IEC 61076-2-109

01



8 poles pin assignment


1/10Gbit	10/100 Mbit	Signals		Pin assignment		4-wire	Cable	
		RJ45		M12 D-coded	M12 X-coded		568A	568B
BI_DA+	TxData+	1		1	1	yellow	white/green	white/orange
BI_DA-	TxData-	2		3	2	orange	green	orange
BI_DB+	RxData+	3		2	3	white	white/orange	white/green
BI_DC+	-	4		-	8		blue	blue
BI_DC-	-	5		-	7		white/blue	white/blue
BI_DB-	RxData-	6		4	4	blue	orange	green
BI_DD+	-	7		-	5		white/brown	white/brown
BI_DD-	-	8		-	6		brown	brown

Adapter M12/RJ45

4 poles pin assignment

10/100 Mbit	RJ45	M12 D-coded	4-wire
TxDATA+	1	1	yellow
TxDATA-	2	3	orange
RxDATA+	3	2	white
RxDATA-	6	4	blue

Stromlaufplan
circuit diagram



Pin assignment




Adapter M12/RJ45

8 poles pin assignment

01

M12	RJ45
1	1
2	2
3	3
4	6
5	7
6	8
7	5
8	4




Gender changer

4 poles




schematic diagram



8 poles



schematic diagram



01
07

01

01
08

Directory

Page

2. ***M8***

2.1 ***A-coded – Solutions for actor and sensor applications***

02

o Technical characteristics	02.02
■ Cable connectors	
• HARAX® M8-XS	02.05
• HARAX® M8-S	02.06
• System cables	02.08
o Accessories	02.12


M8 HARAX® cable connector

Specifications IEC 60 352-4

Approval



Mating face



A-coding
Mating face
acc. to IEC 61 076-2-101

02

Technical characteristics M8 HARAX®

Type M8	HARAX® M8-XS	HARAX® M8-S
---------	--------------	-------------

General data

Conductor cross section	0.1 - 0.14 mm ² AWG 27-26	0.14 - 0.34 mm ² AWG 26-22
Diameter of individual strands	≥ 0.05 mm	≥ 0.1 mm
Conductor insulation material	PVC / PP / TPE	PVC / PP / TPE
Conductor diameter	0.6 - 1.0 mm	1.0 - 1.6 mm
Cable diameter	1.9 - 2.5 mm 2.5 - 3.5 mm	2.5 - 5.1 mm
Temperature range	-40 °C ... +85 °C	-40 °C ... +85 °C
Temperature during connection	-5 °C ... +50 °C	-5 °C ... +50 °C
Degree of protection	IP67	IP67
Mating cycles	100	100
Recommended tightening torque / Hexagonal wrench	0.4 Nm / SW 9	0.4 Nm / SW 9

Electrical characteristics

Rated current	2 A	4 A
Rated voltage	32 V	32 V
Rated impulse voltage	1.5 kV	1.5 kV
Contact resistance	10 mΩ	10 mΩ
Insulation resistance	10 ⁸ Ω	10 ⁸ Ω
Pollution degree	3	3
Overshoot category	3	3
Isolation group	1	1

Materials

Contact material	Copper alloy	Copper alloy
Contact plating	Gold	Gold
Contact carrier material	PA	PA
Housing material	PA, zinc die-cast	PA, zinc die-cast

02
02

Technical characteristics – System cables

M8 Circular connectors, without PE

Rated voltage	max. 60 V AC/DC
Rated current / contact	max. 4 A
Locking	Screw locking M8x1, self securing
Recommended torque	0.4 Nm
Temperature range	-25 °C ... +85 °C (dependant on connected conductor)
Degree of protection	IP67
Number of wires / wire gauge	3 x 0.25 mm ²
Conductor insulation	PP (bn, bu, bk)
Arrangement of insulated strands	32 x 0.1 mm
Sheath	PUR (UL, CSA)
Outer diameter	appr. 4.2 - 5.5 mm
Bending radius	10 x outer diameter
Temperature range (working and storage)	-5 °C ... +80 °C


02

Technical characteristics M8


Current carrying capacity The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity-curve is valid for continuous, not interruptet current-loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.

Control and test procedures according to DIN IEC 60 512-5.

M8-XS, 3 poles 1 = Wire gauge 0.1 mm²
M8-S, 3 poles 2 = Wire gauge 0.14 mm²



M8-S, 4 poles 1 = Wire gauge 0.25 mm²
2 = Wire gauge 0.34 mm²


02
03

02

02
04



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



02

Applications / Advantages

- Actor and sensor applications
- Unshielded versions
- HARAX® rapid termination
- Overmoulded system cables in various lengths
- Robust design, quick assembly

Identification

HARAX® M8-XS




Male
straight version, 3 poles
for 0.1 - 0.14 mm²

Part No.

21 02 159 1305

Drawing




Dimensions in mm

02
05



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



02

Identification


HARAX® M8-S

Male
straight version, 3 poles
for 0.14 - 0.34 mm²

Part No.

21 02 151 1305

Drawing



Male
straight version, 4 poles
for 0.14 - 0.34 mm²


21 02 151 1405

View mating side:
4 poles, male

02
06



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



02

Identification


HARAX® M8-S

Female
straight version, 3 poles
for 0.14 - 0.34 mm²

Part No.

21 02 151 2305

Drawing




Female
straight version, 4 poles
for 0.14 - 0.34 mm²

21 02 151 2405

M8 System cables



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



02

Technical characteristics


M8 Circular connector, without PE

Rated voltage	max. 60 V AC/DC
Rated current/contact	max. 4 A
Locking	Screw locking M8x1, self securing
Recommended torque	0.4 Nm
Temperature range (dependant on connected conductor)	-25 °C ... +85 °C
Degree of protection	IP67
Number of wires / wire gauge	3 x 0.25 mm ²
Conductor insulation	PP (br, bl, sw)
Arrangement of insulated strands	32 x 0.1 mm
Sheath	PUR (UL, CSA)
Outer diameter	appr. 4.2 - 5.5 mm
Bending radius	10 x outer diameter
Temperature range (working and storage)	-5 °C ... + 80 °C

M8 System cables



Mating face



A-coding
Mating face
acc. to IEC 61 076-2-101

02

Overview system cables M8


		Male M8 straight		Female M8 angled	
		Number of contacts		Cable material PUR	
Female M8 angled		0.3 m	21 02 454 5301	xxx	xxx
		0.6 m	21 02 454 5302	xxx	xxx
		1.0 m	21 02 454 5303	xxx	xxx
		1.5 m	21 02 454 5304	xxx	xxx
		2.0 m	21 02 454 5305	xxx	xxx
		0.3 m	21 02 454 7301 with LED	xxx	xxx
		0.6 m	21 02 454 7302 with LED	xxx	xxx
		1.0 m	21 02 454 7303 with LED	xxx	xxx
		1.5 m	21 02 454 7304 with LED	xxx	xxx
		2.0 m	21 02 454 7305 with LED	xxx	xxx
Open end		xxx		1.5 m	21 02 554 4301
		xxx		3.0 m	21 02 554 4302
		xxx		5.0 m	21 02 554 4303
		xxx		7.5 m	21 02 554 4304
		xxx		10.0 m	21 02 554 4305
		xxx		1.5 m	21 02 554 7301 with LED
		xxx		3.0 m	21 02 554 7302 with LED
		xxx		5.0 m	21 02 554 7303 with LED
		xxx		7.5 m	21 02 554 7304 with LED
		xxx		10.0 m	21 02 554 7305 with LED

02
09

M8 System cables



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



02


Identification

M8 Circular connectors
Female angled, male straight

Part No.

Length:	0.3 m	21 02 454 5301
	0.6 m	21 02 454 5302
	1.0 m	21 02 454 5303
	1.5 m	21 02 454 5304
	2.0 m	21 02 454 5305


Drawing



View mating side




Schematic diagram



M8 Circular connectors
Female angled, with LED
Male straight


Length:	0.3 m	21 02 454 7301
	0.6 m	21 02 454 7302
	1.0 m	21 02 454 7303
	1.5 m	21 02 454 7304
	2.0 m	21 02 454 7305



View mating side



Schematic diagram




02
10

M8 System cables



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



02

Identification

M8 Circular connectors


Female angled
pre-assembled on one end

Length:
1.5 m
3.0 m
5.0 m
7.5 m
10.0 m

Part No.


21 02 554 4301
21 02 554 4302
21 02 554 4303
21 02 554 4304
21 02 554 4305

Drawing




Dimensions in mm

Schematic diagram



View mating side




M8 Circular connectors

Female angled, with LED
pre-assembled on one end


Length:
1.5 m
3.0 m
5.0 m
7.5 m
10.0 m

Part No.

21 02 554 7301
21 02 554 7302
21 02 554 7303
21 02 554 7304
21 02 554 7305



Schematic diagram



View mating side



Identification	Part No.	Drawing	Dimensions in mm
Seal M8 for 1.9 - 2.5 mm cable Ø for 2.5 - 3.5 mm cable Ø for 4.2 - 5.4 mm cable Ø	21 01 010 2016 21 01 010 2008 21 01 010 2005		
Set of seals for HARAX® M8-S for 2.5 - 3.2 mm cable Ø for 3.2 - 4.0 mm cable Ø for 4.0 - 5.1 mm cable Ø	21 01 010 2013		
M8 dynamometric screwdriver Tightening torque 0.4 Nm	SW 9	09 99 000 0380	

Directory

Page

3. M12

3.1 A-coded – Solutions for actor and sensor applications

o Technical characteristics	03.04	
■ Cable connectors		
• HARAX® M12-S	03.08	03
• HARAX® M12 angled	03.10	
• HARAX® M12-L unshielded	03.12	
• HARAX® M12-L shielded	03.14	
• M12 Crimp	03.16	
• System cables	03.20	
■ Device connectors		
• Panel feed-through	03.26	
• PCB adapter	03.32	
o Accessories	03.36	

3.2 B-coded – Solutions for Profibus applications

o Technical characteristics	03.40	
■ Cable connectors		
• HARAX® M12 L shielded	03.42	
• M12 Crimp	03.44	
• System cables	03.46	
■ Device connectors		
• Panel feed-through	03.50	
• PCB adapter	03.56	
o Accessories	03.60	

3.3 D-coded – Solutions for Ethernet applications

o Technical characteristics	03.64	
■ Cable connectors		
• HARAX® M12 L shielded	03.66	
• M12 Crimp	03.68	
• M12 preLink®	03.71	
• System cables	03.73	
■ Device connectors		
• Panel feed-through	03.78	
• PCB adapter	03.86	
o Accessories	03.91	03 01

03

03
02

Directory

Page

3.1 A-coded – Solutions for actor and sensor applications

o Technical characteristics	03.04
■ Cable connectors	03
• HARAX® M12-S	03.08
• HARAX® M12 angled	03.10
• HARAX® M12-L unshielded	03.12
• HARAX® M12-L shielded	03.14
• M12 Crimp	03.16
• System cables	03.20
■ Device connectors	
• Panel feed-through	03.26
• PCB adapter	03.32
o Accessories	03.36

03**03**
03

M12 A-coding




Specifications IEC 60 352-4

Approval



Mating face



A-coding
Mating face
acc. to IEC 61 076-2-101

Technical characteristics M12 – A-coding

03

Type M12 A-coded	HARAX® M12-S	HARAX® M12 angled	HARAX® M12 L 3 poles, 4 poles
------------------	--------------	-------------------	-------------------------------

General data

Conductor cross section	0.14 - 0.34 mm ² AWG 26-22	0.25 - 0.5 mm ² AWG 24/7-20	0.34 - 0.75 mm ² AWG 22-18
Diameter of individual strands	≥ 0.1 mm	≥ 0.1 mm	≥ 0.1 mm
Conductor insulation material	PVC / PP / TPE	PVC	PVC
Conductor diameter	1.0 - 1.6 mm	1.2 - 1.6 mm	1.6 - 2.0 mm 2.0 - 2.6 mm
Cable diameter	2.9 - 4.0 mm 4.0 - 5.1 mm	4 - 5.1 mm	6 - 8 mm
Temperature range	-40 °C ... +85 °C	-40 °C ... +85 °C	-40 °C ... +85 °C
Temperature during connection	-5 °C ... +50 °C	-5 °C ... +50 °C	-5 °C ... +50 °C
Degree of protection	IP67	IP67	IP65 / IP67
Mating cycles	100	100	100
Tightening torque connector / hexagonal wrench	0.6 Nm / SW 13	0.6 Nm / SW 13	0.6 Nm / SW 17

Electrical characteristics

Rated current	4 A	4 A	6 A
Rated voltage	32 V	32 V	50 V
Rated impulse voltage	1.5 kV	1.5 kV	1.5 kV
Contact resistance	10 mΩ	10 mΩ	10 mΩ
Insulation resistance	10 ⁸ Ω	10 ⁸ Ω	10 ⁸ Ω
Pollution degree	3	3	3
Overvoltage category	3	3	3
Isolation group	1	1	1

Materials

Contact material	Brass	Brass	Brass
Contact plating	Gold	Gold	Gold
Contact carrier material	PA reinforced	PA	PA unreinforced
Housing material	PA reinforced	PA	PA unreinforced

03
04

M12 A-coding




Specifications IEC 60 352-4

Approval



Mating face



A-coding
Mating face
acc. to IEC 61 076-2-101

Technical characteristics M12 – A-coding

03

Type M12 A-coded	HARAX® M12-L 5 poles	HARAX® M12 L shielded	M12 Crimp
------------------	-------------------------	--------------------------	-----------

General data

Conductor cross section	0.34 - 0.5 mm ² AWG 22-20	0.14 - 0.34 mm ² AWG 26-22	0.14 - 0.75 mm ² AWG 26-18
Diameter of individual strands	≥ 0.1 mm	≥ 0.1 mm	X
Conductor insulation material	PVC	PVC	X
Conductor diameter	1.2 - 2.0 mm	1.2 - 1.6 mm	2.0 - 2.3 mm
Cable diameter	6 - 8 mm	4.5 - 8.8 mm	4.5 - 8.8 mm
Temperature range	-40 °C ... +85 °C	-40 °C ... +85 °C	-40 °C ... +85 °C
Temperature during connection	-5 °C ... +50 °C	-5 °C ... +50 °C	-5 °C ... +50 °C
Degree of protection	IP65 / IP67	IP65 / IP67	IP67
Mating cycles	100	100	500
Tightening torque connector / hexagonal wrench	0.6 Nm / SW 17	0.6 Nm / SW 17	0.5 Nm / SW 17

Electrical characteristics

Rated current	4 A	4 A	4 A
Rated voltage	50 V	50 V	250 V
Rated impulse voltage	1.5 kV	1.5 kV	1.5 kV
Contact resistance	10 mΩ	10 mΩ	10 mΩ
Insulation resistance	10 ⁸ Ω	10 ⁸ Ω	10 ⁸ Ω
Pollution degree	3	3	3
Overvoltage category	3	3	3
Isolation group	1	1	1

Materials

Contact material	Brass	Brass	Brass
Contact plating	Gold	Gold	Gold
Contact carrier material	PA unreinforced	PA unreinforced	PA
Housing material	PA unreinforced	PA unreinforced	PA


03
05

Technical characteristics M12 – A-coding


Current carrying capacity The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity-curve is valid for continuous, not interruptet current-loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.

Control and test procedures according to DIN IEC 60 512-5.


M12-S, 4 poles 1 = Wire gauge 0.25 mm²
 2 = Wire gauge 0.34 mm²




M12-L 1 = Wire gauge 0.34 mm²
 2 = Wire gauge 0.75 mm²




**M12, 4 poles,
angled** 1 = Wire gauge 0.25 mm²
 2 = Wire gauge 0.5 mm²



M12L, 5 poles 1 = Wire gauge 0.25 mm²
 2 = Wire gauge 0.34 mm²



M12, Crimp 1 = Wire gauge 0.34 mm² /
 0.5 mm²



Technical characteristics M12 – A-coding, PCB adapter


M12, A-coding, straight, male, 4 poles
Wire gauge 0.5 mm²




M12, A-coding, straight, female, 4 poles
Wire gauge 0.75 mm²




M12, A-coding, straight, female, 5 poles
Wire gauge 0.5 mm²



M12, A-coding, straight, male, 5 poles
Wire gauge 0.5 mm²





03 Applications / Advantages


- Actor and sensor applications
- Shielded and unshielded versions
- Available with crimp resp. HARAX® rapid termination, or as overmoulded system cable in various lengths
- Robust design, quick assembly

Identification	Part No.	Drawing	Dimensions in mm
HARAX® M12-S	21 03 111 1405		<i>Gesamtlänge im verschraubten Zustand ca. 46,75mm</i> <i>complete length when assembled app. 46,75mm</i>
Male straight version 4 poles, 0.14 - 0.34 mm²	21 03 112 1405		<i>Gesamtlänge im verschraubten Zustand ca. 54,8mm</i> <i>complete length when assembled app. 54,8mm</i>

M12 HARAX® A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

HARAX® M12-S




Female
straight version
4 poles, 0.14 - 0.34 mm²

Part No.

21 03 111 2405


Drawing



Dimensions in mm

Female
straight version
4 poles, 0.25 - 0.5 mm²

21 03 112 2405




03
09

M12 HARAX® A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

HARAX® M12




Male
angled version
4 poles

Part No.

21 01 140 5081

Drawing




Dimensions in mm

03
10

M12 HARAX® A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



Identification

HARAX® M12




Female
angled version
4 poles

Part No.

21 01 140 5091

Drawing




03

03
11

M12 HARAX® A-coded



Mating face





A-coding
Mating face
acc. to IEC 61076-2-101



03


Identification	Part No.	Drawing	Dimensions in mm
HARAX® M12-L, unshielded			
Male 3 poles, A-coding, with pre-leading contact (assignment 3, 4, 5)	21 03 212 1400		
3 poles, A-coding (assignment 1, 3, 4)	21 03 212 1306		
4 poles, A-coding (assignment 1, 2, 3, 4)	21 03 212 1305		
4 poles, A-coding, to 2.6 mm core diameter (assignment 1, 2, 3, 4)	21 03 212 1407		
0.34 - 0.75 mm ² AWG 22 - 18 Cable diameter: 6 - 8 mm			
HARAX® M12-L, unshielded			
Male 5 poles, A-coding	21 03 272 1505		
0.34 - 0.5 mm ² AWG 22 - 20 Cable diameter: 6 - 8 mm			



03
12



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101




Identification	Part No.	Drawing	Dimensions in mm
HARAX® M12-L, unshielded			
Female 3 poles, A-coding (assignment 3, 4, 5)	21 03 212 2400		
3 poles, A-coding (assignment 1, 3, 4)	21 03 212 2306		
4 poles, A-coding (assignment 1, 2, 3, 4)	21 03 212 2305		
4 poles, A-coding, to 2.6 mm core diameter (assignment 1, 2, 3, 4)	21 03 212 2407		
0.34 - 0.75 mm ² AWG 22 - 18 Cable diameter: 6 - 8 mm			
HARAX® M12-L, unshielded			
Female 5 poles, A-coding	21 03 272 2505		
0.34 - 0.5 mm ² AWG 22 - 20 Cable diameter: 6 - 8 mm			

M12 HARAX® A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

HARAX® M12-L, shielded




Male
4 poles, A-coding
0.14 - 0.34 mm² / AWG 26 - 22

Part No.

21 03 221 1405

Drawing




M12 Circular connector



Male
with IDC termination,
8 poles
0.14 - 0.34 mm² / AWG 26 - 22

21 03 121 1801




03
14

M12 HARAX® A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

HARAX® M12-L, shielded




Female
4 poles, A-coding
0.14 - 0.34 mm² / AWG 26 - 22

Part No.

21 03 221 2405

Drawing




Dimensions in mm

M12 Circular connectors




Female
with IDC termination technology,
8 poles
0.14 - 0.34 mm² / AWG 26 - 22

21 03 121 2801



03
15

M12 Crimp A-coded



03

Identification	Part No.	Drawing	Dimensions in mm
M12 Crimp  Male 4 poles, A-coding	21 03 812 1405		Gesamtlänge im verschraubten Zustand ca. 41,5mm complete length when assembled app. 41,5mm M12x1 SW17 Kabel øL,5-5,4mm (transparent) SW15 Kabel ø5,5-7,2mm (schwarz) Kabel ø7-8,8mm (beige)
M12 Crimp  Male 5 poles, A-coding	21 03 812 1505*		Gesamtlänge im verschraubten Zustand ca. 41,5mm complete length when assembled app. 41,5mm M12x1 SW17 Kabel øL,5-5,4mm (transparent) SW15 Kabel ø5,5-7,2mm (schwarz) Kabel ø7-8,8mm (beige)
M12 Crimp Slim design  Male 5 poles, A-coding Cable diameter: 4.5 - 8.8 mm	21 03 821 1505*		Gesamtlänge im verschraubten Zustand ca. 46,1mm complete length when assembled app. 46,1mm M12x1 SW15 width across flats 15 SW4 width across flats 14 SW15 width across flats 15

03
16


Further information and data sheets see www.HARTING.com

* UL approval is in preparation

M12 Crimp A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



Identification

M12 Crimp, angled




Male
5 poles, A-coding

Part No.

21 03 822 3505*

Drawing




03

M12 Crimp A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



03

Identification	Part No.	Drawing	Dimensions in mm
M12 Crimp  Female 4 poles, A-coding	21 03 812 2405		Dimensions in mm
M12 Crimp  Female 5 poles, A-coding	21 03 812 2505*		Dimensions in mm

03
18


Further information and data sheets see www.HARTING.com

* UL approval is in preparation

M12 Crimp A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



Identification

M12 Crimp, angled




Female
5 poles, A-coding

Part No.

21 03 822 4505*

Drawing



03

03
19


Further information and data sheets see www.HARTING.com

* UL approval is in preparation


M12 System cables, A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



Technical characteristics


M12 Circular connectors, without PE

Rated voltage	max. 250 V AC/DC, max. 30 V DC (with LED)
Rated current / contact	max. 4 A
Locking	Screw locking M12x1, self securing
Recommended torque	0.6 Nm
Temperature range	-25 °C ... +85 °C (dependant on connected conductor)
Degree of protection	IP67
Number of wires / wire gauge	4 x 0.34 mm ²
Conductor insulation	PP (bn, wh, bu, bk)
Arrangement of insulated strands	42 x 0.1 mm
Sheath	PUR (UL, CSA)
Outer diameter	appr. 4.7 mm
Bending radius	10 x outer diameter
Temperature range (working and storage)	-25 °C ... + 80 °C


M12 System cables, A-coded



Mating face



A-coding
Mating face
acc. to IEC 61 076-2-101




Overview system cables M12

03

		Male M12 A-coding, straight		Female M12 A-coding, angled	
		Number of contacts		Cable material: PUR	
Female M12	straight		0.3 m	21 03 415 2401	xxx
	straight		0.6 m	21 03 415 2402	xxx
	straight		1.0 m	21 03 415 2403	xxx
	straight		1.5 m	21 03 415 2404	xxx
	straight		2.0 m	21 03 415 2405	xxx
Female M12	angled		0.3 m	21 03 415 5401	xxx
	angled		0.6 m	21 03 415 5402	xxx
	angled		1.0 m	21 03 415 5403	xxx
	angled		1.5 m	21 03 415 5404	xxx
	angled		2.0 m	21 03 415 5405	xxx
Open end		0.3 m	21 03 415 7401 with LED	xxx	
		0.6 m	21 03 415 7402 with LED	xxx	
		1.0 m	21 03 415 7403 with LED	xxx	
		1.5 m	21 03 415 7404 with LED	xxx	
		2.0 m	21 03 415 7405 with LED	xxx	
M12 cable set for individual assembly incl. HARAX® M12 Male		1.5 m	21 03 515 4401	xxx	
		3.0 m	21 03 515 4402	xxx	
		5.0 m	21 03 515 4403	xxx	
		7.5 m	21 03 515 4404	xxx	
		10.0 m	21 03 515 4405	xxx	
M12 cable set for individual assembly incl. HARAX® M12 Male		1.5 m	21 83 515 4401	xxx	
		3.0 m	21 83 515 4402	xxx	
		5.0 m	21 83 515 4403	xxx	
		7.5 m	21 83 515 4404	xxx	
		10.0 m	21 83 515 4405	xxx	
M12 cable set for individual assembly incl. HARAX® M12 Male		1.5 m	21 83 515 7401 with LED	xxx	
		3.0 m	21 83 515 7402 with LED	xxx	
		5.0 m	21 83 515 7403 with LED	xxx	
		7.5 m	21 83 515 7404 with LED	xxx	
		10.0 m	21 83 515 7405 with LED	xxx	

M12 System cables, A-coded





Overview system cables M12

Number of contacts		Male M12 A-coding, straight	
		 Cable material: PUR	
Open end		1.0 m	21 03 514 1801
		2.0 m	21 03 514 1803
		5.0 m	21 03 514 1805

M12 System cables, A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101

Identification

M12 Circular connectors


Female straight, male straight

Length:
0.3 m
0.6 m
1.0 m
1.5 m
2.0 m


Part No.

21 03 415 2401
21 03 415 2402
21 03 415 2403
21 03 415 2404
21 03 415 2405

Drawing



Schematic diagram




M12 Circular connectors


Female angled, male straight

Length:
0.3 m
0.6 m
1.0 m
1.5 m
2.0 m

21 03 415 5401
21 03 415 5402
21 03 415 5403
21 03 415 5404
21 03 415 5405



Schematic diagram




M12 Circular connectors


Female angled, with LED,
Male straight

Length:
0.3 m
0.6 m
1.0 m
1.5 m
2.0 m

21 03 415 7401
21 03 415 7402
21 03 415 7403
21 03 415 7404
21 03 415 7405




Schematic diagram



M12 System cables, A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



03 Identification


M12 Circular connectors

Female angled
pre-assembled on one end

Length:	1.5 m	21 03 515 4401
	3.0 m	21 03 515 4402
	5.0 m	21 03 515 4403
	7.5 m	21 03 515 4404
	10.0 m	21 03 515 4405


Part No.

Drawing



View mating side

Schematic diagram



M12 Circular connectors


Female angled, with LED
pre-assembled on one end

Length:	1.5 m	21 03 515 7401
	3.0 m	21 03 515 7402
	5.0 m	21 03 515 7403
	7.5 m	21 03 515 7404
	10.0 m	21 03 515 7405

Dimensions in mm

View mating side


Schematic diagram



M12 System cables, A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



Identification

Part No.

Drawing


Dimensions in mm

03


HARAX® M12 Cable set without LED

Delivery range: M12 connector with individually adaptable cable and HARAX® M12-S

Length:	1.5 m	21 83 515 4401
	3.0 m	21 83 515 4402
	5.0 m	21 83 515 4403
	7.5 m	21 83 515 4404
	10.0 m	21 83 515 4405




HARAX® M12-S (21 03 111 1405)




HARAX® M12 Cable set with LED

Delivery range: M12 connector with individually adaptable cable and HARAX® M12-S

Length:	1.5 m	21 83 515 7401
	3.0 m	21 83 515 7402
	5.0 m	21 83 515 7403
	7.5 m	21 83 515 7404
	10.0 m	21 83 515 7405




HARAX® M12-S (21 03 111 1405)




1 x M12 Circular connectors, straight

pre-assembled on one end,
8 poles

Length:	1.0 m	21 03 514 1801
	3.0 m	21 03 514 1803
	5.0 m	21 03 514 1805



M12 Panel feed-through HARAX® A-coded



03 Applications / Advantages


- Actor and sensor applications
- For panel feed-through or PCB, straight version in IP20 or IP67, with or without assembled pigtail
- Available with crimp resp. HARAX® rapid termination
- Quick and easy assembly

Identification	Part No.	Drawing	Dimensions in mm
HARAX® Panel feed-through Male 4 poles, A-coding 0.14 - 0.34 mm ² / AWG 26 - 22 Panel thickness min. 2.5 mm max. 4.5 mm	21 03 321 1425		

M12 Panel feed-through HARAX® A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



Identification

HARAX® Panel feed-through




Female
4 poles, A-coding
0.14 - 0.34 mm² / AWG 26 - 22

Panel thickness
min. 2.5 mm
max. 4.5 mm

Part No.

21 03 321 2425

Drawing




03

Dimensions in mm

03
27

M12 Panel feed-through Crimp A-coded



03

Identification

M12 Panel feed-through Crimp




Male
4 poles, A-coding

Panel thickness
min. 2.5 mm
max. 4.5 mm

Part No.

21 03 822 1425

Drawing




M12 Panel feed-through Crimp



Male
5 poles, A-coding

Panel thickness
min. 2.5 mm
max. 4.5 mm

21 03 822 1525*



03
28


Further information and data sheets see www.HARTING.com

* UL approval is in preparation

M12 Panel feed-through Crimp A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

M12 Panel feed-through Crimp




Female
4 poles, A-coding

Panel thickness
min. 2.5 mm
max. 4.5 mm

Part No.

21 03 822 2425

Drawing



Dimensions in mm


M12 Panel feed-through Crimp



Female
5 poles, A-coding

Panel thickness
min. 2.5 mm
max. 4.5 mm


21 03 822 2525*



M12 Panel feed-through A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

M12 Panel feed-through




Male
A-coding,
50 cm conductors, 0.5 mm², 4 poles

Panel thickness
min. 2.0 mm
max. 5.0 mm

Part No.

21 03 311 1402

Drawing



Dimensions in mm


M12 Panel feed-through



Male
A-coding,
50 cm conductors, 0.5 mm², 5 poles

Panel thickness
min. 2.0 mm
max. 5.0 mm

21 03 311 1501




03
30

M12 Panel feed-through A-coded



Mating face




A-coding
Mating face
acc. to IEC 61076-2-101



03

Identification	Part No.	Drawing	Dimensions in mm
<p>M12 Panel feed-through</p>  <p>Female A-coding, 50 cm conductors, 0.5 mm², 4 poles</p> <p>Panel thickness min. 2.0 mm max. 5.0 mm</p>	21 03 311 2400		<p>Dimensions in mm</p>
<p>M12 Panel feed-through</p>  <p>Female A-coding, 50 cm conductors, 0.5 mm², 5 poles</p> <p>Panel thickness min. 2.0 mm max. 5.0 mm</p>	21 03 311 2501		<p>Dimensions in mm</p>

M12 PCB adapter A-coded



Technical characteristics: M12 PCB adapter

03

Degree of protection	IP20, IP67 (mated and locked)	Temperature during connection	-5 °C ... +50 °C
Rated current	max. 4 A (dependant on PCB layout)	Termination	PIH
Rated voltage	50 V	Contact material	Copper alloy
Mating cycles	max. 100	Contact plating (mating side)	Au over Ni
Limiting temperature	-40 °C ... +85 °C	Insulator material	PA


Identification	Part No.	Drawing	Dimensions in mm
M12 PCB adapter Male, A-coding, straight	4 poles, IP20 21 03 321 1410		
M12 PCB adapter Male, A-coding, straight	5 poles, IP20 21 03 321 1510		

03
32

M12 PCB adapter A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



Identification	Part No.	Drawing	Dimensions in mm
M12 PCB adapter Female, A-coding, straight 4 poles, IP20 4 poles, IP67	21 03 321 6410 21 03 321 6420*		Dimensions in mm: 23,55, 6,25, Ø18,5, 3,2, min. 0,5-max. 5,0
M12 PCB adapter Female, A-coding, straight 5 poles, IP20 5 poles, IP67	21 03 321 6510 21 03 321 6520		Dimensions in mm: 23,55, 6,25, Ø18,5, 3,2, min. 0,5-max. 5,0
M12 PCB adapter Female, A-coding, straight 8 poles, IP67	21 03 311 2801		Dimensions in mm: 18, PG9, SW17, max. 4,5


Further information and data sheets see www.HARTING.com

* UL approval is in preparation

M12 PCB adapter shielded A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

M12 PCB adapter,
shielded



Male
5 poles, A-coding



8 poles, A-coding

Part No.

21 03 321 1518*

21 03 321 1818*

Drawing



Dimensions in mm

Housing







for rear mounting

for front mounting

21 03 301 1000

21 03 301 1001



03
34


Further information and data sheets see www.HARTING.com

* UL approval is in preparation

M12 PCB adapter shielded A-coded



Mating face



A-coding
Mating face
acc. to IEC 61076-2-101











Identification	Part No.	Drawing	Dimensions in mm
M12 PCB adapter, shielded			
Female 5 poles, A-coding	21 03 321 2518*		
8 poles, A-coding	21 03 321 2818*		
Housing			
for rear mounting	21 03 301 2000		
for front mounting	21 03 301 2001		

Further information and data sheets see www.HARTING.com

* UL approval is in preparation

Identification	Part No.	Drawing												
M12-male moving load A-coding	21 03 030 1400													
03 HARTING M12 T-Coupler	21 03 321 9400													
Crimping tool for M12 Crimp	09 99 000 0501													
Accessories M12 Crimp		<p>D-Sub contacts</p> <table border="1"> <thead> <tr> <th>Part number</th><th>AWG</th><th>Tool settings</th></tr> </thead> <tbody> <tr> <td>09 67 000 3x76</td><td>18 20 22</td><td>6 6 5</td></tr> <tr> <td>09 67 000 8x76</td><td>20, 22, 24</td><td>6</td></tr> <tr> <td>09 67 000 5x76</td><td>22, 24, 26</td><td>6</td></tr> </tbody> </table>	Part number	AWG	Tool settings	09 67 000 3x76	18 20 22	6 6 5	09 67 000 8x76	20, 22, 24	6	09 67 000 5x76	22, 24, 26	6
Part number	AWG	Tool settings												
09 67 000 3x76	18 20 22	6 6 5												
09 67 000 8x76	20, 22, 24	6												
09 67 000 5x76	22, 24, 26	6												
Locator	09 99 000 0531													
D-Sub single contacts (500 mating cycles)		<p>turned male contacts</p> <table> <tr> <td>AWG 22 - 18 / 0.33 - 0.82 mm²</td> <td>09 67 000 3576</td> </tr> <tr> <td>AWG 24 - 20 / 0.25 - 0.52 mm²</td> <td>09 67 000 8576</td> </tr> <tr> <td>AWG 26 - 22 / 0.13 - 0.33 mm²</td> <td>09 67 000 5576</td> </tr> </table> <p>turned female contacts</p> <table> <tr> <td>AWG 22 - 18 / 0.33 - 0.82 mm²</td> <td>09 67 000 3476</td> </tr> <tr> <td>AWG 24 - 20 / 0.25 - 0.52 mm²</td> <td>09 67 000 8476</td> </tr> <tr> <td>AWG 26 - 22 / 0.13 - 0.33 mm²</td> <td>09 67 000 5476</td> </tr> </table>	AWG 22 - 18 / 0.33 - 0.82 mm ²	09 67 000 3576	AWG 24 - 20 / 0.25 - 0.52 mm ²	09 67 000 8576	AWG 26 - 22 / 0.13 - 0.33 mm ²	09 67 000 5576	AWG 22 - 18 / 0.33 - 0.82 mm ²	09 67 000 3476	AWG 24 - 20 / 0.25 - 0.52 mm ²	09 67 000 8476	AWG 26 - 22 / 0.13 - 0.33 mm ²	09 67 000 5476
AWG 22 - 18 / 0.33 - 0.82 mm ²	09 67 000 3576													
AWG 24 - 20 / 0.25 - 0.52 mm ²	09 67 000 8576													
AWG 26 - 22 / 0.13 - 0.33 mm ²	09 67 000 5576													
AWG 22 - 18 / 0.33 - 0.82 mm ²	09 67 000 3476													
AWG 24 - 20 / 0.25 - 0.52 mm ²	09 67 000 8476													
AWG 26 - 22 / 0.13 - 0.33 mm ²	09 67 000 5476													
M12 dynamometric screwdriver Tightening torque 0.6 Nm		<table border="1"> <thead> <tr> <th>AWG</th><th>a</th></tr> </thead> <tbody> <tr> <td>AWG 22 - 18</td><td>1.34</td></tr> <tr> <td>AWG 24 - 20</td><td>1.13</td></tr> <tr> <td>AWG 26 - 22</td><td>0.88</td></tr> </tbody> </table>	AWG	a	AWG 22 - 18	1.34	AWG 24 - 20	1.13	AWG 26 - 22	0.88				
AWG	a													
AWG 22 - 18	1.34													
AWG 24 - 20	1.13													
AWG 26 - 22	0.88													
for M12-S	SW 13	09 99 000 0382												
for M12 Slim design	SW 15	09 99 000 0646												
for M12-L	SW 17	09 99 000 0384												

Identification	Part No.	Drawing	Dimensions in mm
Seal M12-S for 2.9 - 4.0 mm cable Ø for 4 - 5.1 mm cable Ø	21 01 010 2011 21 01 010 2001		
Seal M12-L unshielded for 4.7 - 6 mm cable Ø for 6 - 8 mm cable Ø	21 01 010 2015 21 01 010 2007		
Set of seals M12-L shielded for 4.5 - 5.4 mm cable Ø for 5.4 - 7.2 mm cable Ø for 7.2 - 8.8 mm cable Ø	21 01 010 2017		
Cap M12 for IP65 / IP67 Seals material Viton Plastic cap for female	21 01 000 0003		
Accessories M12			
Lock nut	21 01 000 0018		

Identification	Part No.	Drawing	Dimensions in mm
Cap metal M12 for IP65 / IP67 M12 metal cap for male side with cord	21 01 000 0033		
Cap metal M12 for IP65 / IP67 M12 metal cap for male side with cable clip	21 01 000 0038		
Cap metal M12 for IP65 / IP67 M12 metal cap for female side with cord	21 01 000 0030		
Cap metal M12 for IP65 / IP67 M12 metal cap for female side with cable clip	21 01 000 0031		

Directory

Page

3.2 B-coded – Solutions for Profibus applications

o Technical characteristics	03.40
	03
■ Cable connectors	
• HARAX® M12 L shielded	03.42
• M12 Crimp	03.44
• System cables	03.46
■ Device connectors	
• Panel feed-through	03.50
• PCB adapter	03.56
o Accessories	03.60

M12 B-coding




Specifications IEC 60 352-4

Approval



Mating face



B-coding
Mating face
acc. to IEC 61076-2-101

Technical characteristics M12 – B-coding

03

Type M12 B-coded	HARAX® M12 L shielded	M12 Crimp
------------------	-----------------------	-----------

General data

Conductor cross section	0.25 - 0.34 mm ² AWG 24-22	0.13 - 0.75 mm ² AWG 26-18
Diameter of individual strands	≥ 0.1 mm	X
Conductor insulation material	PVC, Zell-PE	X
Conductor diameter	2 - 2.6 mm	2.0 - 2.3 mm
Cable diameter	7.0 - 8.8 mm	4 poles: 4.5 - 8.8 mm 5 poles: 4.5 - 8.8 mm
Temperature range	-40 °C ... +85 °C	-40 °C ... +85 °C
Temperature during connection	-5 °C ... +50 °C	-5 °C ... +50 °C
Degree of protection	IP65 / IP67	IP67
Mating cycles	100	500
Tightening torque connector / hexagonal wrench	0.6 Nm / SW 17	0.5 Nm / SW 17

Electrical characteristics

Rated current	4 A	4 A
Rated voltage	32 V	250 V
Rated impulse voltage	1.5 kV	1.5 kV
Contact resistance	10 mΩ	10 mΩ
Insulation resistance	10 ⁸ Ω	10 ⁸ Ω
Pollution degree	3	3
Overvoltage category	3	3
Isolation group	1	1

Materials

Contact material	Brass	Brass
Contact plating	Gold	Gold
Contact carrier material	PA unreinforced	PA
Housing material	PA unreinforced	PA

03
40

Technical characteristics M12 – B-coding


Current carrying capacity The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity-curve is valid for continuous, not interruptet current-loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.

Control and test procedures according to DIN IEC 60 512-5.


03

M12-L
3 poles, 4 poles


1 = Wire gauge 0.34 mm²
2 = Wire gauge 0.75 mm²



M12, Crimp 1 = Wire gauge 0.34 mm² /
 0.5 mm²

03
41

M12 HARAX® B-coded



03 Applications / Advantages


- B-coding for field bus systems e.g. Profibus, DeviceNet or CANopen
- Available with crimp resp. HARAX® rapid termination, or as overmoulded system cable in various lengths
- Shielding by the hood
- Easy handling, quick assembly

Identification	Part No.	Drawing	Dimensions in mm
HARAX® M12-L, shielded  Male 2 poles, B-coding 0.25 - 0.34 mm² / AWG 24 - 22	21 03 241 1301		

M12 HARAX® B-coded



Mating face



B-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

HARAX® M12-L, shielded




Female
2 poles, B-coding
0.25 - 0.34 mm² / AWG 24 - 22

Part No.

21 03 241 2301


Drawing



Dimensions in mm

03
43

M12 Crimp B-coded



03

Identification

M12 Crimp




Male
5 poles, B-coding

Part No.

21 03 841 1505


Drawing

03
44

M12 Crimp B-coded



Mating face



B-coding
Mating face
acc. to IEC 61076-2-101




03

Identification	Part No.	Drawing	Dimensions in mm
M12 Crimp  Female 5 poles, B-coding	21 03 841 2505		03


M12 System cables, B-coding



Mating face



B-coding
Mating face
acc. to IEC 61076-2-101




Technical characteristics

Rated voltage	max. 125 V AC/ DC
Rated current / contact	max. 4 A
Locking	Screw locking M12 x 1 mm, self securing
Recommended tightening torque	0.6 Nm
Temperature range (male) °C	-25 °C ... +85 °C, dependant on connected conductor
Degree of protection	IP67
Number of wires / wire gauge	1 x 2 x diameter 0.64 mm
Conductor insulation	PUR (rd, gn)
Arrangement of insulated strands	19 x 0.13 mm
Sheath	PUR (UL/CSA)
Outer diameter	appr. 7.8 mm
Bending radius bewegt	15 x outer diameter
Temperature range °C (applicable with fixed cable)	-30 °C ... + 80 °C


M12 System cables, B-coding



Mating face






B-coding
Mating face
acc. to IEC 61 076-2-101



Overview system cables M12


03

		Male M12 B-coding	
		straight	angled
Female M12	straight	 Cable material: PUR	
		0.3 m	21 03 449 4301
		0.6 m	21 03 449 4302
		1.0 m	21 03 449 4303
		1.5 m	21 03 449 4304
	angled	2.0 m	21 03 449 4305
Open end		xxx	xxx
		xxx	0.3 m
		xxx	0.6 m
		xxx	1.0 m
		xxx	1.5 m
		xxx	2.0 m
		1.5 m	21 03 549 1301
		3.0 m	21 03 549 1302
		5.0 m	21 03 549 1303
		7.5 m	21 03 549 1304
		10.0 m	21 03 549 1305
		1.5 m	21 03 549 3301
		3.0 m	21 03 549 3302
		5.0 m	21 03 549 3303
		7.5 m	21 03 549 3304
		10.0 m	21 03 549 3305
		Female M12 B-coding	
		straight	angled
Open end		 Cable material: PUR	
		1.5 m	21 03 549 2301
		3.0 m	21 03 549 2302
		5.0 m	21 03 549 2303
		7.5 m	21 03 549 2304
		10.0 m	21 03 549 2305
		 Cable material: PUR	
		1.5 m	21 03 549 4301
		3.0 m	21 03 549 4302
		5.0 m	21 03 549 4303
		7.5 m	21 03 549 4304
		10.0 m	21 03 549 4305


M12 System cables, B-coding



Mating face



B-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

**M12 Circular connectors,
Male, straight**

pre-assembled on one end,
useable as trailing cable

Length:
1.5 m
3.0 m
5.0 m
7.5 m
10.0 m


Part No.

21 03 549 1301
21 03 549 1302
21 03 549 1303
21 03 549 1304
21 03 549 1305

Darstellung



Schematic diagram



**M12 Circular connectors,
Male, angled**


pre-assembled on one end,
useable as trailing cable

Length:
1.5 m
3.0 m
5.0 m
7.5 m
10.0 m

21 03 549 3301
21 03 549 3302
21 03 549 3303
21 03 549 3304
21 03 549 3305



Schematic diagram




03
48


M12 System cables, B-coding



Mating face



B-coding
Mating face
acc. to IEC 61076-2-101



Identification

**M12 Circular connectors,
Female, straight**

pre-assembled on one end,
useable as trailing cable

Length:	1.5 m	21 03 549 2301
	3.0 m	21 03 549 2302
	5.0 m	21 03 549 2303
	7.5 m	21 03 549 2304
	10.0 m	21 03 549 2305

**M12 Circular connectors,
Female, angled**

pre-assembled on one end,
useable as trailing cable

Length:	1.5 m	21 03 549 4301
	3.0 m	21 03 549 4302
	5.0 m	21 03 549 4303
	7.5 m	21 03 549 4304
	10.0 m	21 03 549 4305

**M12 Circular connectors,
Male, straight
Female, straight**

pre-assembled on one end,
useable as trailing cable

Length:	0.3 m	21 03 449 4301
	0.6 m	21 03 449 4302
	1.0 m	21 03 449 4303
	1.5 m	21 03 449 4304
	2.0 m	21 03 449 4305

**M12 Circular connectors,
Male, angled
Female, angled**



pre-assembled on one end,
useable as trailing cable

Length:	0.3 m	21 03 449 6301
	0.6 m	21 03 449 6302
	1.0 m	21 03 449 6303
	1.5 m	21 03 449 6304
	2.0 m	21 03 449 6305


Darstellung





Schematic diagram




Schematic diagram




Schematic diagram



Schematic diagram




M12 Panel feed-through HARAX® B-coded



03 Applications / Advantages


- B-coding for field bus systems e.g. Profibus, DeviceNet or CANopen
- For panel feed-through or PCB, straight version in IP20 or IP67, with or without assembled pigtail
- Available with crimp resp. HARAX® rapid termination
- Quick and easy assembly

Identification	Part No.	Drawing	Dimensions in mm
<p>HARAX® Panel feed-through</p>  <p>Male 2 poles and shielding, B-coding 0.25 - 0.34 mm² / AWG 24 - 22 Cable diameter: 7 - 8.8 mm Panel thickness min. 2.5 mm max. 4.5 mm</p>	21 03 341 1425		<p>Gesamtlänge im verschraubten Zustand ca. 57mm complete length when assembled app. 57mm</p> <p>Width across flats 17</p> <p>Width across flats 17</p> <p>Width across flats 13</p> <p>Width across flats 13</p> <p>20</p> <p>18.4</p> <p>M12x1.5</p> <p>M12x1.5</p> <p>15.4 10.2</p> <p>15.4 10.2</p>

M12 Panel feed-through HARAX® B-coded



Mating face



B-coding
Mating face
acc. to IEC 61076-2-101



Identification


HARAX® Panel feed-through



Part No.

21 03 341 2425

Drawing



Dimensions in mm


03

Female
2 poles and shielding, B-coding
0.25 - 0.34 mm² / AWG 24 - 22

Cable diameter: 7 - 8.8 mm

Panel thickness
min. 2.5 mm
max. 4.5 mm

M12 Panel feed-through Crimp B-coded



03

Identification

M12 Panel feed-through
Crimp




Male
5 poles, B-coding

Panel thickness
min. 2.5 mm
max. 4.5 mm

Part No.

21 03 841 1525


Drawing

03
52

M12 Panel feed-through Crimp B-coded



Mating face



B-coding
Mating face
acc. to IEC 61076-2-101



Identification

M12 Panel feed-through
Crimp




Female
5 poles, B-coding

Panel thickness
min. 2.5 mm
max. 4.5 mm

Part No.

21 03 841 2525

Drawing




Dimensions in mm



03

03
53

M12 Panel feed-through B-coded



03


Identification	Part No.	Drawing	Dimensions in mm
<p>M12 Panel feed-through</p>  <p>Male B-coding, 20 cm conductors, 0.25 mm²</p> <p>Panel thickness min. 2.0 mm max. 5.0 mm</p>	21 03 339 1301	 <p>Technical drawing showing dimensions for the M12 Panel feed-through B-coded connector. Key dimensions include: - Total length: 26.1 mm - Thread length: 14 +0.2 mm - Width across flats: 14 mm - Dichtung/sealing width: SW14 - Thread: M16x1.5 - Pinout: 1 (bottom), 2 (left), 3 (right), 4 (top), 5 (center)</p>	
<p>M12-male/female panel feed-through B-coding</p>  <p>Panel thickness min. 2.0 mm max. 5.0 mm</p>	21 03 330 1300	 <p>Technical drawing showing dimensions for the M12-male/female panel feed-through B-coded connector. Key dimensions include: - Total height: max. 35 mm - Thread length: 10.5 mm - Thread: M12x1 - Pinout: 1 (bottom), 2 (left), 3 (right), 4 (top), 5 (center)</p>	<p>Rated voltage: 24 V AC/DC Thread: M16 x 1.5</p>

03
54

M12 Panel feed-through B-coded



Mating face



B-coding
Mating face
acc. to IEC 61076-2-101



Identification

M12 Panel feed-through




Female
B-coding, 20 cm conductors,
0.25 mm²

Panel thickness
min. 2.0 mm
max. 5.0 mm

Part No.

21 03 339 2301


Drawing



Dimensions in mm

03

M12 PCB adapter B-coded



Technical characteristics: M12 PCB adapter


Degree of protection	IP20, IP67 (mated and locked)	Temperature during connection	-5 °C ... +50 °C
Rated current	max. 4 A (dependant on PCB layout)	Termination	PIH
Rated voltage	50 V	Contact material	Copper alloy
Mating cycles	max. 100	Contact plating (mating side)	Au over Ni
Limiting temperature	-40 °C ... +85 °C	Insulator material	PA

Identification	Part No.	Drawing	Dimensions in mm
M12 PCB adapter Male, B-coding, straight 	5 poles, IP20 21 03 341 1505		

M12 PCB adapter B-coded



Mating face



B-coding
Mating face
acc. to IEC 61076-2-101



Identification

M12 PCB adapter

Female, B-coding,
straight






5 poles, IP20

Part No.

21 03 341 2505

Drawing



Dimensions in mm


03

03
57

M12 PCB adapter shielded B-coded



Mating face



B-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

M12 PCB adapter,
shielded





Male
5 poles, B-coding

Part No.

21 03 341 1518*

Drawing



Dimensions in mm

Housing




for rear mounting

for front mounting

21 03 301 1000

21 03 301 1001



03
58


Further information and data sheets see www.HARTING.com

* UL approval is in preparation

M12 PCB adapter shielded B-coded



Mating face



B-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

M12 PCB adapter,
shielded




Female
5 poles, B-coding

Part No.

21 03 341 2518*

Drawing



Dimensions in mm

Housing




for rear mounting

21 03 301 2000

for front mounting

21 03 301 2001



Further information and data sheets see www.HARTING.com

* UL approval is in preparation

03
59

Identification

Part No.

Drawing

Crimping tool
for M12 Crimp

09 99 000 0501



03

Accessories M12 Crimp

Locator

09 99 000 0531



D-Sub contacts

Part number	AWG	Tool settings
09 67 000 3x76	18	6
	20	6
	22	5
09 67 000 8x76	20, 22, 24	6
09 67 000 5x76	22, 24, 26	6

D-Sub single contacts (500 mating cycles)

turned male contacts

AWG 22-18 / 0.33-0.82 mm²

AWG 24-20 / 0.25-0.52 mm²

AWG 26-22 / 0.13-0.33 mm²



09 67 000 3576

09 67 000 8576

09 67 000 5576

turned female contacts

AWG 22-18 / 0.33-0.82 mm²

AWG 24-20 / 0.25-0.52 mm²


AWG 26-22 / 0.13-0.33 mm²



09 67 000 3476

09 67 000 8476

09 67 000 5476



a
AWG 22-18
AWG 24-20
AWG 26-22

M12 dynamometric screwdriver

Tightening torque 0.6 Nm

for M12-S SW 13

09 99 000 0382

for M12-L SW 17

09 99 000 0384



Cap M12



for IP65 / IP67

Seals material Viton

Plastic cap for female



21 01 000 0003



03
60

Identification	Part No.	Drawing	Dimensions in mm
Cap metal M12 for IP65 / IP67 M12 metal cap for male side with cord	21 01 000 0033		03
Cap metal M12 for IP65 / IP67 M12 metal cap for male side with cable clip	21 01 000 0038		
Cap metal M12 for IP65 / IP67 M12 metal cap for female side with cord	21 01 000 0030		
Cap metal M12 for IP65 / IP67 M12 metal cap for female side with cable clip	21 01 000 0031		03

Identification	Part No.	Drawing	Dimensions in mm
M12-male moving load B-coding 	21 03 030 1300		
HARTING M12 T-Coupler	21 03 341 6401		
Seal M12-L unshielded for 4.7 - 6 mm cable Ø for 6 - 8 mm cable Ø 	21 01 010 2015 21 01 010 2007		
Set of seals M12-L shielded for 4.5 - 5.4 mm cable Ø for 5.4 - 7.2 mm cable Ø for 7.2 - 8.8 mm cable Ø 	21 01 010 2017		
Accessories M12 Lock nut 	21 01 000 0018		

Directory

Page

3.3 D-coded – Solutions for Ethernet applications

o Technical characteristics	03.64
	03
■ Cable connectors	
• HARAX® M12 L shielded	03.66
• M12 Crimp	03.68
• M12 preLink®	03.71
• System cables	03.73
■ Device connectors	
• Panel feed-through	03.78
• PCB adapter	03.86
o Accessories	03.91

M12 D-coding




Specifications IEC 60 352-4

Approval



Mating face



D-coding
Mating face
acc. to IEC 61076-2-101

Technical characteristics M12 – D-coding

03

Type M12 D-coded	HARAX® M12 L shielded	M12 Crimp	M12 preLink®
------------------	-----------------------	-----------	--------------

General data

Conductor cross section	0.14 - 0.34 mm ² AWG 26-22 0.34 - 0.5 mm ² AWG 22-20	0.13 - 0.75 mm ² AWG 26-18	0.10 - 0.34 mm ² AWG 27-22
Diameter of individual strands	≥ 0.1 mm	X	≥ 0.1 mm
Conductor insulation material	PVC/PE	X	PVC/PE
Conductor diameter	1.2 - 2.0 mm	2.0 - 2.3 mm	0.8 - 1.6 mm
Cable diameter	4.5 - 8.8 mm	4 poles: 4.5 - 8.8 mm 5 poles: 4.5 - 8.8 mm	6.3 - 6.7 mm
Temperature range	-40 °C ... +85 °C	-40 °C ... +85 °C	-40 °C ... +85 °C
Temperature during connection	-5 °C ... +50 °C	-5 °C ... +50 °C	–
Degree of protection	IP65 / IP67	IP67	IP65
Mating cycles	100	500	250
Tightening torque connector / Hexagonal wrench	0.6 Nm / SW 17	0.6 Nm / SW 17	0.6 Nm / SW 17

Electrical characteristics

Rated current	4 A	4 A	1 A
Rated voltage	50 V	250 V	48 V
Rated impulse voltage	1.5 kV	1.5 kV	1.5 kV
Contact resistance	10 mΩ	10 mΩ	10 mΩ
Insulation resistance	10 ⁸ Ω	10 ⁸ Ω	10 ⁸ Ω
Pollution degree	3	3	3
Overshoot category	3	3	3
Isolation group	1	1	–
Transmission performance (Category)	Cat. 5	Cat. 5	Cat. 5

Materials

Contact material	Brass	Brass	Brass
Contact plating	Gold	Gold	Gold
Contact carrier material	PA unreinforced	PA	–
Housing material	PA unreinforced	PA	Zinc die-cast

03
64

Technical characteristics M12 – D-coding


Current carrying capacity The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity-curve is valid for continuous, not interruptet current-loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.

Control and test procedures according to DIN IEC 60 512-5.

M12-L


3 poles, 4 poles

1 = Wire gauge 0.34 mm²
2 = Wire gauge 0.75 mm²



M12, Crimp

1 = Wire gauge 0.34 mm² /
0.5 mm²




03

Technical characteristics M12 – D-coding, PCB adapter


M12, D-coding, straight, female, 4 poles

Wire gauge 0.5 mm²




M12, D-coding, angled, female, 4 poles

Wire gauge AWG 22



03
65



03 Applications / Advantages


- D-coding for Ethernet/Profinet applications
- Robust design
- 360° shielding termination
- Transmission performance Cat. 5

Identification	Part No.	Drawing	Dimensions in mm
HARAX® M12-L, shielded	21 03 281 1405		
Male 4 poles, D-coding 0.14 - 0.34 mm², AWG 26 - 22	21 03 282 1405		

M12 HARAX® D-coded



Mating face



D-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

HARAX® M12-L, shielded




Female
4 poles, D-coding
0.14 - 0.34 mm², AWG 26 - 22

Part No.

21 03 281 2405

Drawing



Dimensions in mm

Female
4 poles, D-coding
0.34 - 0.5 mm², AWG 22 - 20


21 03 282 2405

03
67

M12 Crimp D-coded



Mating face



D-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

M12 Crimp, shielded




Male
4 poles, D-coding

Part No.

21 03 882 1405


Drawing



Male
4 poles, D-coding

21 03 882 1415

Dimensions in mm




03
68

M12 Crimp D-coded



Mating face



D-coding
Mating face
acc. to IEC 61076-2-101



Identification

M12 Crimp Slim design, shielded




Male
4 poles, D-coding
Cable: 4.4 - 8.8 mm
outer diameter

Part No.

21 03 881 1405*

Drawing




Dimensions in mm

M12 Crimp, shielded




Male
4 poles, D-coding
angled

21 03 882 3405*



03

M12 Crimp D-coded



03

Identification

M12 Crimp, shielded




Female
4 poles, D-coding


Part No.

21 03 882 2405

Drawing

03
70

M12 preLink® D-coded



03

Identification


preLink® M12 housing



Part No.

20 82 000 1210

Drawing




Dimensions in mm

preLink® M12 male module

Male
4 poles, D-coding



20 82 005 1214



preLink® terminal module

(Pack with 10 pieces)
terminal block with IDC termination

Number of contacts: 8

Conductor cross section: AWG 22/23 (24)
solid and stranded




Conductor diameter: Ø 1.3 - 1.6 mm
Colour: yellow

Conductor cross section: AWG 26/27
solid and stranded

Conductor diameter: Ø 0.8 - 1.1 mm
Colour: white

20 82 000 0001

20 82 000 0003




Assembly tool

20 82 000 9901


M12 System cables, D-coding



Mating face



D-coding
Mating face
acc. to IEC 61 076-2-101



Technical characteristics

Pre-assembled and tested system cables

for structured cabling of industrial Ethernet networks, based on M12 Circular connectors, D-coded

Cable type:	Shielded Twisted Pair Standard Cable
Mating interface:	M12 D-coded acc. to IEC 61 076-2-101
Transmission performance acc. to ISO/IEC 11801:2002:	Class D, 100% tested
Degree of protection	IP65 / IP67 (when mated)

Pin assignment

Signal	Function	Conductor colour PROFInet®	Contact assignment
TD+	Transmission Data+	Yellow	1
TD-	Transmission Data-	Orange	3
RD+	Receiver Data+	White	2
RD-	Receiver Data-	Blue	4

03

03
73

M12 System cables, D-coding



03

Overview system cables M12

Number of contacts			Male M12 D-coding straight	
Male M12	straight		Cable material: PUR	
			1.0 m	21 03 485 1401 09 48 222 2004 010*
			1.5 m	21 03 485 1451 09 48 222 2004 015*
			3.0 m	21 03 485 1403 09 48 222 2004 030*
			5.0 m	21 03 485 1405 09 48 222 2004 050*
			7.5 m	21 03 485 1457 09 48 222 2004 075*
			10.0 m	21 03 485 1410 09 48 222 2004 100*
			20.0 m	21 03 485 1420 09 48 222 2004 200*
Open end			Cable material: PVC	
Open end			1.0 m	09 47 222 2002 09 48 222 2003 010*
			1.5 m	09 47 222 2003 09 48 222 2003 015*
			3.0 m	09 47 222 2005 09 48 222 2003 030*
			5.0 m	09 47 222 2006 09 48 222 2003 050*
			7.5 m	09 47 222 2022 09 48 222 2003 075*
			10.0 m	09 47 222 2011 09 48 222 2003 100*
			20.0 m	09 47 222 2013 09 48 222 2003 200*

* Mid 2014 the part numbers beginning with 21 03 ... or 09 47 ... will be replaced by the part numbers beginning with 09 48 ...
The former part numbers will be set to status inactive.

Please use only the part numbers beginning with 09 48 ... for your order.



03
74

M12 System cables, D-coding



Overview system cables M12

03

Number of contacts			Male M12 D-coding angled	
Male M12	angled		Cable material: PUR	
			1.0 m	21 03 485 3401 09 48 808 0004 010*
			1.5 m	21 03 485 3451 09 48 808 0004 015*
			3.0 m	21 03 485 3403 09 48 808 0004 030*
			5.0 m	21 03 485 3405 09 48 808 0004 050*
			7.5 m	21 03 485 3457 09 48 808 0004 075*
			10.0 m	21 03 485 3410 09 48 808 0004 100*
			20.0 m	21 03 485 3420 09 48 808 0004 200*
Open end			Cable material: PVC	
Open end			1.0 m	09 47 808 0002 09 48 808 0003 010*
			1.5 m	09 47 808 0003 09 48 808 0003 015*
			3.0 m	09 47 808 0005 09 48 808 0003 030*
			5.0 m	09 47 808 0006 09 48 808 0003 050*
			7.5 m	09 47 808 0022 09 48 808 0003 075*
			10.0 m	09 47 808 0011 09 48 808 0003 100*
			20.0 m	09 47 808 0013 09 48 808 0003 200*

* Mid 2014 the part numbers beginning with 21 03 ... or 09 47 ... will be replaced by the part numbers beginning with 09 48 ...
The former part numbers will be set to status inactive.
Please use only the part numbers beginning with 09 48 ... for your order.




Identification	Part No.	Drawing	Dimensions in mm
2 x M12 Circular connectors, D-coding, PUR, straight			
Length*: 1.0 m 1.5 m 3.0 m 5.0 m 7.5 m 10.0 m 20.0 m	21 03 485 1401 21 03 485 1451 21 03 485 1403 21 03 485 1405 21 03 485 1457 21 03 485 1410 21 03 485 1420		Cable: AWG 22 / 0.34 mm ²
1 x M12 Circular connectors, D-coding, PUR, straight			
Length*: 1.0 m 1.5 m 3.0 m 5.0 m 7.5 m 10.0 m 20.0 m	21 03 585 1401 21 03 585 1451 21 03 585 1403 21 03 585 1405 21 03 585 1457 21 03 585 1410 21 03 585 1420		Cable: AWG 22 / 0.34 mm ²
2 x M12 Circular connectors, D-coding, PUR, angled			
Length*: 1.0 m 1.5 m 3.0 m 5.0 m 7.5 m 10.0 m 20.0 m	21 03 485 3401 21 03 485 3451 21 03 485 3403 21 03 485 3405 21 03 485 3457 21 03 485 3410 21 03 485 3420		Cable: AWG 22 / 0.34 mm ²
1 x M12 Circular connectors, D-coding, PUR, angled			
Length*: 1.0 m 1.5 m 3.0 m 5.0 m 7.5 m 10.0 m 20.0 m	21 03 585 3401 21 03 585 3451 21 03 585 3403 21 03 585 3405 21 03 585 3457 21 03 585 3410 21 03 585 3420		Cable: AWG 22 / 0.34 mm ²




Identification	Part No.	Drawing	Dimensions in mm
2 x M12 Circular connectors, D-coding, PVC, straight			
Length*: 1.0 m 1.5 m 3.0 m 5.0 m 7.5 m 10.0 m 20.0 m	09 47 222 2002 09 47 222 2003 09 47 222 2005 09 47 222 2006 09 47 222 2022 09 47 222 2011 09 47 222 2013	Cable: AWG 22 / 0.34 mm ² 	
1 x M12 Circular connectors, D-coding, PVC, straight			
Length*: 1.0 m 1.5 m 3.0 m 5.0 m 7.5 m 10.0 m 20.0 m	09 47 220 0002 09 47 220 0003 09 47 220 0005 09 47 220 0006 09 47 220 0022 09 47 220 0011 09 47 220 0013	Cable: AWG 22 / 0.34 mm ² 	
2 x M12 Circular connectors, D-coding, PVC, angled			
Length*: 1.0 m 1.5 m 3.0 m 5.0 m 7.5 m 10.0 m 20.0 m	09 47 808 0002 09 47 808 0003 09 47 808 0005 09 47 808 0006 09 47 808 0022 09 47 808 0011 09 47 808 0013	Cable: AWG 22 / 0.34 mm ² 	
1 x M12 Circular connectors, D-coding, PVC, angled			
Length*: 1.0 m 1.5 m 3.0 m 5.0 m 7.5 m 10.0 m 20.0 m	09 47 800 0002 09 47 800 0003 09 47 800 0005 09 47 800 0006 09 47 800 0022 09 47 800 0011 09 47 800 0013	Cable: AWG 22 / 0.34 mm ² 	

M12 Panel feed-through HARAX® D-coded



03 Applications / Advantages


- D-coding for Ethernet/Profinet applications
- Patent HARAX® fast termination
- Robust design
- 360° shielding termination
- Transmission performance Cat. 5

Identification	Part No.	Drawing	Dimensions in mm
HARAX® Panel feed-through  Male 4 poles, D-coding 0.14 - 0.34 mm² / AWG 26 - 22 Panel thickness min. 2.5 mm max. 4.5 mm	21 03 381 1425		Gesamtlänge im verschraubten Zustand ca. 51,5mm complete length when assembled app. 51,5mm 18,4 M12x1 M16x1,5 M16x1 SW17 width across flats 17 Kabel/cable Ø4,5-5,4mm (transparent/transparent) Kabel/cable Ø5,5-7,2mm (schwarz/black) Kabel/cable Ø7-8,8mm (beige/beige) SW20 Ø16,3±0,2 15,4±0,2

M12 Panel feed-through HARAX® D-coded



Mating face



D-coding
Mating face
acc. to IEC 61076-2-101



Identification

HARAX® Panel feed-through




Female
4 poles, D-coding
0.14 - 0.34 mm² / AWG 26 - 22

Panel thickness
min. 2.5 mm
max. 4.5 mm

Part No.

21 03 381 2425


Drawing



03

Dimensions in mm

M12 Panel feed-through Crimp D-coded



03

Identification

M12 Panel feed-through Crimp




Male
4 poles, D-coding

Panel thickness
min. 2.5 mm
max. 4.5 mm

Part No.

21 03 882 1425

Drawing




Dimensions in mm

03
80

M12 Panel feed-through Crimp D-coded



Mating face



D-coding
Mating face
acc. to IEC 61076-2-101



Identification

M12 Panel feed-through Crimp




Female
4 poles, D-coding

Panel thickness
min. 2.5 mm
max. 4.5 mm

Part No.


21 03 882 2425

Drawing



03

M12 Panel feed-through D-coded



03

Identification




M12 Panel feed-through



Part No.

21 03 371 1403

Drawing



Dimensions in mm

Male
D-coding
50 cm conductors, AWG 22, 4 poles


Panel thickness
min. 2.0 mm
max. 5.0 mm

03
82

M12 Panel feed-through D-coded



Mating face



D-coding
Mating face
acc. to IEC 61076-2-101



Identification

M12 Panel feed-through





Female
D-coding
50 cm conductors, AWG 22, 4 poles

Panel thickness
min. 2.0 mm
max. 5.0 mm

Part No.

21 03 371 2403

Drawing




Dimensions in mm

03

03
83

M12 Panel feed-through D-coded



03

Identification

**M12 Female-RJ45
Panel feed-through**



4 poles, D-coding
angled

Panel thickness
min. 2.1 mm
max. 4.5 mm

**M12 Female-RJ45
Panel feed-through**



4 poles, D-coding
straight

Panel thickness
min. 2.1 mm
max. 4.5 mm

M12 Male-RJ45 Adapter



4 poles, D-coding
straight
(coupler, without thread in the
termination area)

Part No.

21 03 381 4400





21 03 381 4401*

21 03 381 2400

21 03 381 2401*

21 03 371 1420

Drawing



Dimensions in mm

03

84


Further information and data sheets see www.HARTING.com

* UL approval is in preparation

M12 Panel feed-through D-coded



Mating face



D-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

M12 Gender Changer
Female-Female



4 poles, D-coding
Cat. 5

M12 Gender Changer
Female-Female



4 poles, D-coding
Cat. 5

Wall bracket





Part No.

21 03 381 6405




21 03 381 6401*

21 01 000 0036

Drawing




Panel cut out
(1:1)



Dimensions in mm

M12 PCB adapter D-coded



Technical characteristics: M12 PCB adapter D-coded angled


Degree of protection	IP20, IP67 (mated and locked)	Temperature during connection	-5 °C ... +50 °C
Rated current	max. 4 A (dependant on PCB layout)	Termination	Reflow
Rated voltage	50 V	Contact material	Copper alloy
Mating cycles	max. 100	Contact plating (mating side)	Au over Ni
Limiting temperature	-40 °C ... +85 °C	Insulator material	LCP

Identification	Part No.	Drawing	Dimensions in mm
M12 PCB adapter Male, D-coding, straight  4 poles, IP67	21 03 371 1400		

M12 PCB adapter D-coded



Mating face



D-coding
Mating face
acc. to IEC 61076-2-101



Identification

M12 PCB adapter

Female, D-coding,
straight




4 poles, IP67

Part No.

21 03 371 2415

Drawing




Dimensions in mm

03




4 poles, IP20
4 poles, IP67

21 03 381 6410
21 03 381 6420



M12 PCB adapter D-coded



Identification

M12 PCB adapter

Female, D-coding,
angled, 4 poles

without fixing hole

IP20

21 03 381 4410¹⁾

IP20

21 03 381 4411²⁾

IP67

21 03 381 4430¹⁾



with fixing hole

IP20

21 03 381 4412¹⁾

IP20

21 03 381 4413²⁾

IP67





21 03 381 4432¹⁾




Part No.

Drawing


Dimensions in mm



1) Cable direction
to the right




2) Cable direction
to the bottom



M12 PCB adapter shielded D-coded



Mating face



D-coding
Mating face
acc. to IEC 61076-2-101



03

Identification

M12 PCB adapter,
shielded




Male
4 poles, D-coding

Part No.

21 03 381 1418*

Drawing



Dimensions in mm

Housing




for rear mounting

21 03 301 1000

for front mounting

21 03 301 1001




03
89

Further information and data sheets see www.HARTING.com

* UL approval is in preparation

M12 PCB adapter shielded D-coded



03

Identification

M12 PCB adapter,
shielded





Female
4 poles, D-coding

Part No.

21 03 381 2418*

Drawing



Dimensions in mm

Housing




for rear mounting

21 03 301 2000

for front mounting

21 03 301 2001



03
90

Further information and data sheets see www.HARTING.com

* UL approval is in preparation

Identification	Part No.	Drawing																		
Crimping tool for M12 Crimp	09 99 000 0501																			
Accessories M12 Crimp																				
Locator	09 99 000 0531																			
D-Sub single contacts (500 mating cycles)		<p>D-Sub contacts</p> <table border="1"> <thead> <tr> <th>Part number</th> <th>AWG</th> <th>Tool settings</th> </tr> </thead> <tbody> <tr> <td>09 67 000 3x76</td> <td>18</td> <td>6</td> </tr> <tr> <td>09 67 000 8x76</td> <td>20</td> <td>6</td> </tr> <tr> <td>09 67 000 5x76</td> <td>22</td> <td>5</td> </tr> <tr> <td>09 67 000 20, 22, 24</td> <td>20, 22, 24</td> <td>6</td> </tr> <tr> <td>09 67 000 22, 24, 26</td> <td>22, 24, 26</td> <td>6</td> </tr> </tbody> </table>	Part number	AWG	Tool settings	09 67 000 3x76	18	6	09 67 000 8x76	20	6	09 67 000 5x76	22	5	09 67 000 20, 22, 24	20, 22, 24	6	09 67 000 22, 24, 26	22, 24, 26	6
Part number	AWG	Tool settings																		
09 67 000 3x76	18	6																		
09 67 000 8x76	20	6																		
09 67 000 5x76	22	5																		
09 67 000 20, 22, 24	20, 22, 24	6																		
09 67 000 22, 24, 26	22, 24, 26	6																		
turned male contacts AWG 22-18 / 0.33-0.82 mm ² AWG 24-20 / 0.25-0.52 mm ² AWG 26-22 / 0.13-0.33 mm ²	09 67 000 3576 09 67 000 8576 09 67 000 5576																			
turned female contacts AWG 22-18 / 0.33-0.82 mm ² AWG 24-20 / 0.25-0.52 mm ² AWG 26-22 / 0.13-0.33 mm ²	09 67 000 3476 09 67 000 8476 09 67 000 5476																			
M12 dynamometric screwdriver																				
Tightening torque 0.6 Nm																				
for M12 Slim design	SW 15	09 99 000 0646																		
for M12-L	SW 17	09 99 000 0384																		
Set of seals M12-L shielded for 4.5 - 5.4 mm cable Ø for 5.4 - 7.2 mm cable Ø for 7.2 - 8.8 mm cable Ø	21 01 010 2017																			
Accessories M12																				
Lock nut	21 01 000 0018																			

Identification	Part No.	Drawing	Dimensions in mm
Cap metal M12 for IP65 / IP67 M12 metal cap for male side with cord	21 01 000 0033		
Cap metal M12 for IP65 / IP67 M12 metal cap for male side with cable clip	21 01 000 0038		
Cap metal M12 for IP65 / IP67 M12 metal cap for female side with cord	21 01 000 0030		
Cap metal M12 for IP65 / IP67 M12 metal cap for female side with cable clip	21 01 000 0031		
Cap M12 for IP65 / IP67 Seals material Viton Plastic cap for female	21 01 000 0003		

Directory

Page

4. har-speed M12 data connectors

4.1 X-coded – Solutions for high-speed applications

o Technical characteristics	04.02	04
■ Cable connectors		
• har-speed M12 connector	04.05	
• System cables	04.06	
■ Device connectors		
• har-speed M12 Panel feed-through	04.07	
• har-speed PCB connector	04.09	
o Accessories	04.13	

M12 X-coding




Specifications IEC 60 352-4

Approval



Mating face



X-coding
Mating face
acc. to IEC 61076-2-101

Technical characteristics M12 – X-coding

Type M12 X-coded	har-speed M12 har-speed M12 Slim design
------------------	--

04

General data

Conductor cross section	0.08 - 0.25 mm ² AWG 28-23
Diameter of individual strands	–
Conductor insulation material	–
Conductor diameter	0.33 - 0.61 mm
Cable diameter	4.5 - 8.8 mm
Temperature range	-40 °C ... +85 °C
Temperature during connection	-5 °C ... +50 °C
Degree of protection	IP65 / IP67
Mating cycles	500
Tightening torque connector / hexagonal wrench	0.6 Nm / SW 15

Electrical characteristics

Rated current	0.5 A
Rated voltage	48 V
Rated impulse voltage	1.5 kV
Contact resistance	15 mΩ
Insulation resistance	10 ⁸ Ω
Pollution degree	3
Overshoot category	3
Isolation group	1
Transmission performance (Category)	Cat. 6A

Materials

Contact material	Brass
Contact plating	Gold
Contact carrier material	LCP
Housing material	ZP410

04
02

Further information and data sheets see www.HARTING.com


* UL approval is in preparation

Technical characteristics M12 – X-coding

Current carrying capacity The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity-curve is valid for continuous, not interruptet current-loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.


Control and test procedures according to DIN IEC 60 512-5.

har-speed M12
8 poles




04

har-speed M12
PCB adapter

04
03

04

04
04



Applications / Advantages

- High-Speed Ethernet applications for process automatization, e.g. camera system for process control in the production
- Maximum data rates through the configuration of the contacts in conformance with Ethernet technology. Transfer class E_A for 1 and 10 Gigabit
- Perfect shielding through paired shielding of the contacts
- Overmoulded system cables in various lengths


04

Identification	Part No.	Drawing	Dimensions in mm		
har-speed M12  Male straight version 8 poles, Cat. 6A Cable diameter: 4.5 - 8.8 mm	21 03 881 5805	 Male straight version 8 poles, Cat. 6A Cable diameter: 4.5 - 8.8 mm	21 03 881 1805		

har-speed M12 System cables X-coded



Mating face



X-coding
Mating face
acc. to IEC 61076-2-101




Identification	Part No.	Drawing	Dimensions in mm	
har-speed M12 System cables single ended overmoulded system cable				
Length: 1 m 3 m 5 m 7 m 10 m	21 03 483 1801 21 03 483 1803 21 03 483 1805 21 03 483 1807 21 03 483 1810			
double ended overmoulded system cable				
Length: 0.5 m 1.0 m 1.5 m 2.0 m 2.5 m	21 03 483 5850 21 03 483 5801 21 03 483 5851 21 03 483 5802 21 03 483 5852			

har-speed M12 Panel feed-through X-coded



Mating face



X-coding
Mating face
acc. to IEC 61076-2-101



Identification

har-speed M12
Adapter M12-RJ45






straight, Cat. 6A

Panel thickness
min. 2.1 mm
max. 4.5 mm

Part No.

21 03 381 2800

Drawing



Dimensions in mm



04



angled, Cat. 6A


Panel thickness
min. 2.1 mm
max. 4.5 mm

21 03 381 4800



04
07

har-speed M12 Panel feed-through X-coded



Identification


Gender changer, Cat. 6A



Part No.

21 03 381 6815

Drawing





Dimensions in mm

Wall bracket




21 01 000 0036



har-speed M12 PCB adapter X-coded



Mating face



X-coding
Mating face
acc. to IEC 61076-2-101



Identification

har-speed M12 PCB adapter


Female, X-coding,
straight, Cat. 6A
for front mounting




Part No.

21 03 381 2802

Drawing



Dimensions in mm





har-speed M12 PCB adapter

Female, X-coding,
straight, Cat. 5
for front mounting



21 03 381 2803





har-speed M12 PCB adapter


Female, X-coding,
angled, Cat. 6A
for front mounting



21 03 381 4802



har-speed M12 PCB adapter X-coded



Identification

har-speed M12 PCB adapter


Female, X-coding,
straight, Cat. 6A
for rear mounting




Part No.

21 03 381 2804

Drawing



Dimensions in mm





har-speed M12 PCB adapter

Female, X-coding,
straight, Cat. 5
for rear mounting



21 03 381 2805





har-speed M12 PCB adapter

Female, X-coding,
angled, Cat. 6A
for rear mounting




21 03 381 4804



har-speed M12 PCB adapter X-coded



Mating face



X-coding
Mating face
acc. to IEC 61076-2-101



Identification

**har-speed M12
PCB adapter**



Female
8 poles, X-coding
Cat. 6A

Female
8 poles, X-coding
Cat. 5

Housing



for rear mounting



for front mounting

Part No.

21 03 381 2806

21 03 381 2807

Drawing




04

har-speed M12 PCB adapter X-coded



Mating face



X-coding
Mating face
acc. to IEC 61076-2-101



Identification

har-speed M12
PCB adapter



Female, X-coding,
straight, Cat. 6A
for front mounting




Part No.

21 03 381 2801

Drawing



Bohrplan/drilling plan
Bestückungsseite (Frontansicht)
plug-in side (front view)



04

04
12

Identification	Part No.	Drawing																					
Crimping tool for har-speed M12	09 99 000 0501																						
Accessories har-speed M12																							
Locator	09 99 000 0525																						
Single contacts (500 mating cycles)																							
<i>har-speed M12 contacts</i> AWG 28-24 / 0.08-0.22 mm ²	21 01 100 9014	<table border="1"><caption>har-speed contacts</caption><thead><tr><th>Part number</th><th>AWG</th><th>Tool settings</th></tr></thead><tbody><tr><td>21 01 100 9014</td><td>28</td><td>3</td></tr><tr><td></td><td>26</td><td>4</td></tr><tr><td></td><td>24</td><td>5</td></tr><tr><td>21 01 100 9019</td><td>26</td><td>4</td></tr><tr><td></td><td>24</td><td>5</td></tr><tr><td></td><td>23</td><td>5</td></tr></tbody></table>	Part number	AWG	Tool settings	21 01 100 9014	28	3		26	4		24	5	21 01 100 9019	26	4		24	5		23	5
Part number	AWG	Tool settings																					
21 01 100 9014	28	3																					
	26	4																					
	24	5																					
21 01 100 9019	26	4																					
	24	5																					
	23	5																					
<i>har-speed M12 contacts</i> AWG 26-23 / 0.13-0.25 mm ²	21 01 100 9019																						
Accessories M12																							
Lock nut	21 01 000 0018																						
M12 dynamometric screwdriver																							
Tightening torque 0.6 Nm																							
for M12 Slim design SW 15	09 99 000 0646																						

Identification	Part No.	Drawing	Dimensions in mm
Cap metal M12 for IP65 / IP67 M12 metal cap for male side with cord	21 01 000 0033		
04 Cap metal M12 for IP65 / IP67 M12 metal cap for male side with cable clip	21 01 000 0038		
Cap metal M12 for IP65 / IP67 M12 metal cap for female side with cord	21 01 000 0030		
Cap metal M12 for IP65 / IP67 M12 metal cap for female side with cable clip	21 01 000 0031		
Cap M12 for IP65 / IP67 Seals material Viton Plastic cap for female	21 01 000 0003		

Directory

Page

5. 7/8" HARAX®

5.1 7/8" HARAX®-Power-Circular connectors

o Technical characteristics	05.02
■ Cable connectors	
• 7/8" HARAX® Male	05.04
• 7/8" HARAX® Female	05.05
• System cables	05.06
■ Device connectors	
• Panel feed-through	05.10
o Accessories	05.12

05

05
01

7/8" HARAX®




Specifications IEC 60 352-4
DIN 61984

Approval VDE



Mating face



Mating face
acc. to IEC 61076-2-101

Technical characteristics 7/8" HARAX®

Type	7/8" HARAX®
------	-------------

General data

Conductor cross section	0.75 - 1.5 mm ² AWG 18-16
Diameter of individual strands	≥ 0.15 mm
Conductor insulation material	PVC, PP, TPE
Conductor diameter	≤ 2.8 mm
Cable diameter	6.8 - 9.5 mm (black) 9 - 12.5 mm (grey)
Temperature range	-40 °C ... +85 °C
Temperature during connection	-5 °C ... +50 °C
Degree of protection	IP65 / IP67
Mating cycles	100
Recommended tightening torque / Hexagonal wrench	1.5 Nm / SW 22

Electrical characteristics

Rated current	10 A
Rated voltage	230 V / 400 V
Rated impulse voltage	4.8 kV
Contact resistance	10 mΩ
Insulation resistance	10 ⁸ Ω
Pollution degree	3
Overshoot category	3
Isolation group	1

Materials

Contact material	Copper alloy
Contact plating	Gold
Contact carrier material	TPU, PA
Housing material	TPU, zinc die-cast, PA

Technical characteristics – System cables, 7/8" HARAX®

Degree of protection	IP67
Temperature range applies to moved cable cables permanently installed	-20 °C ... +80 °C -50 °C ... +80 °C
Rated current	max. 8 A every contact (+40 °C)
Rated voltage	230 / 400 V
Rated impulse voltage	3 kV
Pollution degree	3
Material group	Category I acc. to IEC 60664-1

Cable data

05


Jacket material	PUR
Jacket colour	grey
Wire isolation	TPM
Wire colours	brown, white, blue, black, green/yellow
Wire gauge	5 x 1.5 mm ²
Standards	UL / CSA

Technical characteristics 7/8" HARAX®

Current carrying capacity The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity-curve is valid for continuous, not interruptet current-loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.

Control and test procedures according to DIN IEC 60512-5.

7/8"


1 = Wire gauge 0.75 mm² /
1.5 mm²

05

03



Mating face



Mating face
acc. to IEC 61 076-2-101



Applications / Advantages

- The reliable connector for power applications
- Patent HARAX® fast termination
- Overmoulded system cables in various lengths
- Robust design, quick assembly

05

Identification


7/8" HARAX® Male



Part No.

21 04 116 1505

Drawing




Dimensions in mm

05
04



Mating face

Mating face
acc. to IEC 61076-2-101

Identification


7/8" HARAX® Female



Part No.

21 04 116 2505

Drawing



Dimensions in mm



05

05

7/8" System cables



Mating face



Mating face
acc. to IEC 61076-2-101

Technical characteristics

Degree of protection	IP67
Temperature range applies to moved cable cables permanently installed	-20 °C ... +80 °C -50 °C ... +80 °C
Rated current	max. 8 A every contact (+40 °C)
Rated voltage	230 / 400 V
Rated impulse voltage	3 kV
Pollution degree	3
Material group	Category I acc. to IEC 60664-1



Cable data

Jacket material	PUR
Jacket colour	grey
Wire isolation	TPM
Wire colours	brown, white, blue, black, green/yellow
Wire gauge	5 x 1.5 mm ²
Standards	UL / CSA

7/8" System cables










Mating face





Mating face
acc. to IEC 61 076-2-101

Overview system cables 7/8"

Number of contacts			Male 7/8"	
Female 7/8"	straight		straight	
			angled	
				Cable material: PUR
			0.3 m	21 04 416 1501
			0.6 m	21 04 416 1502
	angled		1.0 m	21 04 416 1503
	angled		1.5 m	21 04 416 1504
	angled		2.0 m	21 04 416 1505
Number of contacts			Female 7/8"	
Open end			straight	
			angled	
				Cable material: PUR
			1.5 m	21 04 516 2501
			3.0 m	21 04 516 2502
	Open end		5.0 m	21 04 516 2503
	Open end		7.5 m	21 04 516 2504
	Open end		10.0 m	21 04 516 2505

7/8" System cables



Identification	Part No.	Drawing	Dimensions in mm
Overmoulded cordsets 7/8" Female straight 3 poles Length: 2.0 m	21 04 516 2302	 Schematic diagram	 
Overmoulded cordsets 7/8" Male straight 4 poles Length: 2.0 m	21 04 516 1402	 Schematic diagram	 

05

05
08




Identification	Part No.	Drawing	Dimensions in mm
Overmoulded cordsets 7/8"			
Female straight 5 poles			
Length:			
1.5 m	21 04 516 2501		
3.0 m	21 04 516 2502		
5.0 m	21 04 516 2503		
7.5 m	21 04 516 2504		
10.0 m	21 04 516 2505		
		Schematic diagram	View mating side
Overmoulded cordsets 7/8"			
Female angled 5 poles			
Length:			
1.5 m	21 04 516 4501		
3.0 m	21 04 516 4502		
5.0 m	21 04 516 4503		
7.5 m	21 04 516 4504		
10.0 m	21 04 516 4505		
		Schematic diagram	View mating side
Overmoulded cordsets 7/8"			
Male-Female straight 5 poles			
Length:			
0.3 m	21 04 416 1501		
0.6 m	21 04 416 1502		
1.0 m	21 04 416 1503		
1.5 m	21 04 416 1504		
2.0 m	21 04 416 1505		
		Schematic diagram	View mating side
Overmoulded cordsets 7/8"			
Male-Female angled 5 poles			
Length:			
0.3 m	21 04 416 3501		
0.6 m	21 04 416 3502		
1.0 m	21 04 416 3503		
1.5 m	21 04 416 3504		
2.0 m	21 04 416 3505		
		Schematic diagram	View mating side

7/8“ Panel feed-through



Mating face



Mating face
acc. to IEC 61076-2-101



Identification


7/8“ Panel feed-through
20 cm conductors, AWG 18, 1 mm², 3 poles

Male

Part No.

21 04 316 1305

Drawing




Dimensions in mm

7/8“ Panel feed-through
50 cm conductors, AWG 18, 1 mm², 5 poles

Male


21 04 316 1505



7/8“ Panel feed-through



Mating face



Mating face
acc. to IEC 61076-2-101



Identification

7/8“ Panel feed-through


20 cm conductors, AWG 18, 1 mm², 4 poles

Female

Part No.

21 04 316 2400

Drawing




Dimensions in mm

7/8“ Panel feed-through

50 cm conductors, AWG 18, 1 mm², 5 poles

Female

21 04 316 2505



05

05
11

Identification


Lock nut Pg 13.5
nickel plated




Part No.

21 01 000 0020

Drawing



Dimensions in mm



05

7/8"
dynamometric screwdriver

Tightening torque 1.5 Nm

for 7/8" SW 23

09 99 000 0395

05
12

Directory

Page

6. HARAX® Panel feed-through

6.1 HARAX® Panel feed-through

o Technical characteristics	06.02
■ Cable connectors	
• HARAX® Pg 13.5 / M20 Panel feed-through	06.04
o Accessories	06.05

06

HARAX® Panel feed-through

Specifications IEC 60 352-4
DIN 61984

Approval VDE



Technical characteristics Panel feed-through

Type	HARAX® Pg 13.5/M20 Panel feed-through
------	---------------------------------------

General data

Conductor cross section	0.75 - 1.5 mm ² AWG 18 - 16
Diameter of individual strands	≥ 0.2 mm
Conductor insulation material	PVC, PP, TPE
Conductor diameter	≤ 2.8 mm
Cable diameter	6 - 9 mm
Temperature range	-25 °C ... +85 °C
Temperature during connection	-5 °C ... +50 °C
Degree of protection	IP67
Mating cycles	100
Recommended tightening torque	8 Nm

Electrical characteristics

Rated current	16 A
Rated voltage	230 V / 400 V
Rated impulse voltage	4 KV
Contact resistance	10 mΩ
Insulation resistance	10 ⁸ Ω
Pollution degree	3
Oversupply category	3
Isolation group	1

Materials

Contact material	Copper alloy
Contact plating	Gold
Contact carrier material	TPU, PA
Housing material	TPU, PA

Technical characteristics Panel feed-through


Current carrying capacity The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity-curve is valid for continuous, not interruptet current-loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.

Control and test procedures according to DIN IEC 60 512-5.

Pg 13.5
3 poles

1 = Wire gauge
0.75 mm²


2 = Wire gauge
1.5 mm²



Pg 13.5 / M20
4 poles

1 = Wire gauge
0.75 mm²

2 = Wire gauge
1.5 mm²





Identification	Part No.	Drawing	Dimensions in mm
HARAX® Pg 13.5 / 3 contacts with faston blades	21 01 130 1013		Gesamtlänge im verschraubten Zustand ca. 49,6mm Complete length when assembled app. 49,6mm
HARAX® Pg 13.5 / 3 contacts with solder termination	21 01 130 1023		Gesamtlänge im verschraubten Zustand ca. 49,6mm Complete length when assembled app. 49,6mm
HARAX® Pg 13.5 / 3 contacts with pre-assembled pigtail cable, l = 500 mm, 1.5 mm²	21 01 130 1223		Gesamtlänge im verschraubten Zustand ca. 49,6mm Complete length when assembled app. 49,6mm
HARAX® Pg 13.5 / 2 + PE with faston blades	21 01 130 3013		Gesamtlänge im verschraubten Zustand ca. 49,6mm Complete length when assembled app. 49,6mm
HARAX® Pg 13.5 / 2 + PE with solder termination	21 01 130 3023		Gesamtlänge im verschraubten Zustand ca. 49,6mm Complete length when assembled app. 49,6mm
HARAX® Pg 13.5 / 2 + PE with pre-assembled pigtail cable, l = 500 mm, 1.5 mm²	21 01 130 3233		Gesamtlänge im verschraubten Zustand ca. 49,6mm Complete length when assembled app. 49,6mm
HARAX® Pg 13.5 / 4 contacts with solder termination	21 01 140 1023		Gesamtlänge im verschraubten Zustand ca. 48,2mm Complete length when assembled app. 48,2mm
HARAX® Pg 13.5 / 3 + PE with solder termination	21 01 140 3023		Gesamtlänge im verschraubten Zustand ca. 48,2mm Complete length when assembled app. 48,2mm
HARAX® Pg 13.5 / 4 contacts with pre-assembled pigtail cable, l = 500 mm, 1.5 mm²	21 01 140 1323		Gesamtlänge im verschraubten Zustand ca. 48,2mm Complete length when assembled app. 48,2mm
HARAX® Pg 13.5 / 3 + PE with pre-assembled pigtail cable, l = 500 mm, 1.5 mm²	21 01 140 3333		
HARAX® M20 / 4 contacts with solder termination	21 01 141 1023		Gesamtlänge im verschraubten Zustand ca. 48,2mm Complete length when assembled app. 48,2mm
HARAX® M20 / 3 + PE with solder termination	21 01 141 3023		Gesamtlänge im verschraubten Zustand ca. 48,2mm Complete length when assembled app. 48,2mm
HARAX® M20 / 4 contacts with pre-assembled pigtail cable, l = 500 mm, 1.5 mm²	21 01 141 1323		Gesamtlänge im verschraubten Zustand ca. 48,2mm Complete length when assembled app. 48,2mm
HARAX® M20 / 3 + PE with pre-assembled pigtail cable, l = 500 mm, 1.5 mm²	21 01 141 3333		

Identification		Part No.	Drawing	Dimensions in mm
Termination element M12 HARAX® Pg 9 Screw cap, splice ring, seal	3 contacts	21 01 010 0001		
Termination element M12 HARAX® Pg 9 Screw cap, splice ring, seal	4 contacts	21 01 010 0006		
Lock nut Pg 9		21 01 000 0008		
Lock nut Pg 13.5, SW 27		21 01 000 0007		
Lock nut Pg 13.5, SW 24		21 01 000 0039		

06

06
05

Directory

Page

7. INOX – Solutions for extreme demands

7.1 M12 INOX

o Technical characteristics	07.02
■ Cable connectors	
• M12-L INOX	07.04

07

07
01

Specifications IEC 60 352-4
IEC 60 068-2-52:1996, severity level 4



Technical characteristics M12 INOX

Type M12 INOX V4A	HARAX® M12-L 4 poles	M12 Crimp
-------------------	-------------------------	-----------

General data

Conductor cross section	0.34 - 0.75 mm ² AWG 22 - 18	0.14 - 0.75 mm ² AWG 26 - 18
Diameter of individual strands	≥ 0.1 mm	X
Conductor insulation material	PVC	X
Conductor diameter	1.6 - 2.0 mm 2.0 - 2.6 mm	2.0 - 2.3 mm
Cable diameter	6 - 8 mm	4.5 - 8.8 mm
Temperature range	-40 °C ... +85 °C	-40 °C ... +85 °C
Temperature during connection	-5 °C ... +50 °C	-5 °C ... +50 °C
Degree of protection	IP65 / IP67	IP67
Mating cycles	100	500
Tightening torque connector / hexagonal wrench	0.6 Nm / SW 17	0.6 Nm / SW 17

Electrical characteristics

Rated current	6 A	4 A
Rated voltage	50 V	250 V
Rated impulse voltage	1.5 kV	1.5 kV
Contact resistance	10 mΩ	10 mΩ
Insulation resistance	10 ⁸ Ω	10 ⁸ Ω
Pollution degree	3	3
Overtvoltage category	3	3
Isolation group	1	1

Materials


Contact material	Brass	Brass
Contact plating	Gold	Gold
Contact carrier material	PA unreinforced	PA
Housing material	V4A	V4A

Technical characteristics M12 INOX


Current carrying capacity The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity-curve is valid for continuous, not interruptet current-loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature.

Control and test procedures according to DIN IEC 60 512-5.

M12-L
4 poles





M12, Crimp 1 = Wire gauge 0.34 mm² /
 0.5 mm²





Mating faces

A-coding
4 poles
Mating faces acc. to IEC 61076-2-101A-coding
5 poles
Mating faces acc. to IEC 61076-2-101

Applications / Advantages


- Designed for rough outdoor applications in harsh environments
- Material V4A
- Available with crimp resp. HARAX® rapid termination
- Extreme robust design, quick assembly

07


Identification	Part No.	Drawing	Dimensions in mm
HARAX® M12-L INOX	21 03 222 2435		Dimensions in mm
Female, A-coding, straight version 4 poles			
M12-L Crimp INOX	21 03 822 2535	<p>Gesamtlänge im verschraubten Zustand ca.41,4mm complete length when assembled app. 41,4mm</p> <p>Montagehilfe wird lose beigelegt assembly aid enclosed</p>	Dimensions in mm



Mating faces



B-coding



D-coding

Mating faces acc. to IEC 61076-2-101



Identification

M12-L Crimp INOX




Male, B-coding,
straight version
5 poles

Part No.

21 03 841 1535

Drawing




07



Male, D-coding,
straight version
4 poles

21 03 882 1435



07
05

List of part numbers



Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page	Part No.	Page
09 47 220 0002	03.74	09 48 220 0004 075	03.74	09 99 000 0382	03.60	21 01 010 2017	03.62	21 02 554 7305	02.09
09 47 220 0002	03.77	09 48 220 0004 100	03.74	09 99 000 0384	03.36	21 01 010 2017	03.91	21 02 554 7305	02.11
09 47 220 0003	03.74	09 48 220 0004 200	03.74	09 99 000 0384	03.60				
09 47 220 0003	03.77			09 99 000 0384	03.91	21 01 100 9014	04.13		
09 47 220 0005	03.74	09 48 222 2003 010	03.74	09 99 000 0395	05.12	21 01 100 9019	04.13	21 03 030 1300	03.62
09 47 220 0005	03.77	09 48 222 2003 015	03.74	09 99 000 0501	03.36			21 03 030 1400	03.36
09 47 220 0006	03.74	09 48 222 2003 030	03.74	09 99 000 0501	03.91	21 01 130 1013	06.04		
09 47 220 0006	03.77	09 48 222 2003 050	03.74	09 99 000 0501	04.13	21 01 130 1023	06.04	21 03 111 1405	03.08
09 47 220 0011	03.74	09 48 222 2003 075	03.74	09 99 000 0525	04.13	21 01 130 1223	06.04	21 03 111 2405	03.09
09 47 220 0011	03.77	09 48 222 2003 100	03.74	09 99 000 0531	03.36	21 01 130 3013	06.04		
09 47 220 0013	03.74	09 48 222 2003 200	03.74	09 99 000 0531	03.60	21 01 130 3023	06.04	21 03 112 1405	03.08
09 47 220 0013	03.77	09 48 222 2004 010	03.74	09 99 000 0531	03.91	21 01 130 3233	06.04	21 03 112 2405	03.09
09 47 220 0022	03.74	09 48 222 2004 015	03.74	09 99 000 0646	03.36				
09 47 220 0022	03.77	09 48 222 2004 030	03.74	09 99 000 0646	03.91	21 01 140 1023	06.04		
		09 48 222 2004 050	03.74	09 99 000 0646	04.13	21 01 140 1323	06.04	21 03 121 1801	03.14
09 47 222 2002	03.74	09 48 222 2004 075	03.74			21 01 140 3023	06.04	21 03 121 2801	03.15
09 47 222 2002	03.77	09 48 222 2004 100	03.74			21 01 140 3333	06.04		
09 47 222 2003	03.74	09 48 222 2004 200	03.74			21 01 140 5081	03.10	21 03 212 1305	03.12
09 47 222 2003	03.77					21 01 140 5091	03.11	21 03 212 1306	03.12
09 47 222 2005	03.74	09 48 800 0003 010	03.75	20 82 000 0001	03.71			21 03 212 1400	03.12
09 47 222 2005	03.77	09 48 800 0003 015	03.75	20 82 000 0003	03.71	21 01 141 1023	06.04	21 03 212 1407	03.12
09 47 222 2006	03.74	09 48 800 0003 030	03.75	20 82 000 1210	03.71	21 01 141 1323	06.04	21 03 212 2305	03.13
09 47 222 2006	03.77	09 48 800 0003 050	03.75	20 82 000 9901	03.71	21 01 141 3023	06.04	21 03 212 2306	03.13
09 47 222 2011	03.74	09 48 800 0003 075	03.75			21 01 141 3333	06.04	21 03 212 2400	03.13
09 47 222 2011	03.77	09 48 800 0003 100	03.75	20 82 005 1214	03.71			21 03 212 2407	03.13
09 47 222 2013	03.74	09 48 800 0003 200	03.75			21 02 151 1305	02.06		
09 47 222 2013	03.77	09 48 800 0004 010	03.75			21 02 151 1405	02.06	21 03 221 1405	03.14
09 47 222 2022	03.74	09 48 800 0004 015	03.75			21 02 151 2305	02.07	21 03 221 2405	03.15
09 47 222 2022	03.77	09 48 800 0004 030	03.75			21 02 151 2405	02.07		
09 47 800 0002	03.75	09 48 800 0004 050	03.75	21 01 000 0003	03.37			21 03 222 2435	07.04
09 47 800 0002	03.77	09 48 800 0004 075	03.75	21 01 000 0003	03.60				
09 47 800 0003	03.75	09 48 800 0004 100	03.75	21 01 000 0003	03.92	21 02 159 1305	02.05		
09 47 800 0003	03.77	09 48 800 0004 200	03.75	21 01 000 0003	04.14			21 03 241 1301	03.42
09 47 800 0003	03.77			21 01 000 0007	06.05			21 03 241 2301	03.43
09 47 800 0005	03.75	09 48 808 0003 010	03.75	21 01 000 0008	06.05	21 02 454 5301	02.09		
09 47 800 0005	03.77	09 48 808 0003 015	03.75	21 01 000 0018	03.37	21 02 454 5301	02.10	21 03 272 1505	03.12
09 47 800 0006	03.75	09 48 808 0003 030	03.75	21 01 000 0018	03.62	21 02 454 5302	02.09	21 03 272 2505	03.13
09 47 800 0006	03.77	09 48 808 0003 050	03.75	21 01 000 0018	03.91	21 02 454 5302	02.10		
09 47 800 0011	03.75	09 48 808 0003 075	03.75	21 01 000 0018	04.13	21 02 454 5303	02.09	21 03 281 1405	03.66
09 47 800 0011	03.77	09 48 808 0003 100	03.75	21 01 000 0020	05.12	21 02 454 5303	02.10	21 03 281 2405	03.67
09 47 800 0013	03.75	09 48 808 0003 200	03.75	21 01 000 0030	03.38	21 02 454 5304	02.09		
09 47 800 0013	03.77	09 48 808 0004 010	03.75	21 01 000 0030	03.61	21 02 454 5304	02.10		
09 47 800 0022	03.75	09 48 808 0004 015	03.75	21 01 000 0030	03.92	21 02 454 5305	02.09	21 03 282 1405	03.66
09 47 800 0022	03.77	09 48 808 0004 030	03.75	21 01 000 0030	04.14	21 02 454 5305	02.10	21 03 282 2405	03.67
09 47 808 0002	03.75	09 48 808 0004 050	03.75	21 01 000 0031	03.38	21 02 454 7301	02.09		
09 47 808 0002	03.77	09 48 808 0004 075	03.75	21 01 000 0031	03.61	21 02 454 7301	02.10	21 03 301 1000	03.34
09 47 808 0003	03.75	09 48 808 0004 100	03.75	21 01 000 0031	03.92	21 02 454 7302	02.09	21 03 301 1000	03.58
09 47 808 0003	03.77	09 48 808 0004 200	03.75	21 01 000 0031	04.14	21 02 454 7302	02.10	21 03 301 1000	03.89
09 47 808 0003	03.77			21 01 000 0033	03.38	21 02 454 7303	02.09	21 03 301 1001	03.34
09 47 808 0005	03.75			21 01 000 0033	03.61	21 02 454 7303	02.10	21 03 301 1001	03.58
09 47 808 0005	03.77	09 67 000 3476	03.36	21 01 000 0033	03.92	21 02 454 7304	02.09	21 03 301 1001	03.89
09 47 808 0006	03.75	09 67 000 3476	03.60	21 01 000 0036	03.85	21 02 454 7305	02.09	21 03 301 2000	03.35
09 47 808 0006	03.77	09 67 000 3476	03.91	21 01 000 0036	04.08	21 02 454 7305	02.10	21 03 301 2000	03.59
09 47 808 0011	03.75	09 67 000 3576	03.36	21 01 000 0038	03.38			21 03 301 2000	03.90
09 47 808 0011	03.77	09 67 000 3576	03.60	21 01 000 0038	03.61	21 02 454 7306	02.09	21 03 301 2000	04.11
09 47 808 0013	03.75	09 67 000 3576	03.91	21 01 000 0038	03.92	21 02 454 7306	02.10	21 03 301 2001	03.35
09 47 808 0013	03.77	09 67 000 5476	03.36	21 01 000 0038	04.14	21 02 454 7305	02.09	21 03 301 2001	03.59
09 47 808 0022	03.75	09 67 000 5476	03.60	21 01 000 0039	06.05	21 02 454 7305	02.10	21 03 301 2001	03.90
09 47 808 0022	03.77	09 67 000 5476	03.91			21 02 454 7306	02.09	21 03 301 2001	04.11
		09 67 000 5576	03.36	21 01 010 0001	06.05	21 02 454 7306	02.11		
		09 67 000 5576	03.60	21 01 010 0006	06.05	21 02 454 7304	02.09	21 03 311 1402	03.30
		09 67 000 5576	03.91	21 01 010 0001	03.37	21 02 454 7304	02.11	21 03 311 1501	03.30
		09 67 000 8476	03.36	21 01 010 0005	02.12	21 02 454 7305	02.09	21 03 311 2400	03.31
		09 67 000 8476	03.60	21 01 010 0007	03.37	21 02 454 7305	02.11	21 03 311 2501	03.31
		09 67 000 8476	03.91	21 01 010 0007	03.62	21 02 454 7301	02.09	21 03 311 2801	03.33
		09 67 000 8576	03.36	21 01 010 0008	02.12	21 02 454 7301	02.11		
		09 67 000 8576	03.60	21 01 010 0011	03.37	21 02 454 7302	02.09	21 03 321 1410	03.32
		09 67 000 8576	03.91	21 01 010 0013	02.12	21 02 454 7302	02.11	21 03 321 1420	03.32
				21 01 010 0015	03.37	21 02 454 7303	02.09	21 03 321 1425	03.26
				21 01 010 0015	03.62	21 02 454 7303	02.11	21 03 321 1510	03.32
		09 99 000 0380	02.12	21 01 010 0016	02.12	21 02 454 7304	02.09	21 03 321 1518	03.34
		09 99 000 0382	03.36	21 01 010 0017	03.37	21 02 454 7304	02.11	21 03 321 1520	03.32

Be

List of part numbers



Part No.	Page								
21 03 321 1818	03.34	21 03 415 5401	03.23	21 03 485 3410	03.76	21 03 549 4304	03.49	21 04 316 1305	05.10
21 03 321 2425	03.27	21 03 415 5402	03.21	21 03 485 3420	03.75	21 03 549 4305	03.47	21 04 316 1505	05.10
21 03 321 2518	03.35	21 03 415 5402	03.23	21 03 485 3420	03.76	21 03 549 4305	03.49	21 04 316 2400	05.11
21 03 321 2818	03.35	21 03 415 5403	03.21	21 03 485 3451	03.75			21 04 316 2505	05.11
21 03 321 6410	03.33	21 03 415 5403	03.23	21 03 485 3451	03.76	21 03 585 1401	03.74		
21 03 321 6420	03.33	21 03 415 5404	03.21	21 03 485 3457	03.75	21 03 585 1401	03.76	21 04 416 1501	05.07
21 03 321 6510	03.33	21 03 415 5404	03.23	21 03 485 3457	03.76	21 03 585 1403	03.74	21 04 416 1501	05.09
21 03 321 6520	03.33	21 03 415 5405	03.21			21 03 585 1405	03.74	21 04 416 1502	05.07
21 03 321 9400	03.36	21 03 415 5405	03.23	21 03 514 1801	03.22	21 03 585 1410	03.74	21 04 416 1502	05.09
		21 03 415 7401	03.21	21 03 514 1801	03.25	21 03 585 1405	03.76	21 04 416 1503	05.07
21 03 330 1300	03.54	21 03 415 7401	03.23	21 03 514 1803	03.22	21 03 585 1410	03.74	21 04 416 1503	05.09
		21 03 415 7402	03.21	21 03 514 1803	03.25	21 03 585 1410	03.76	21 04 416 1504	05.07
21 03 339 1301	03.54	21 03 415 7403	03.21	21 03 514 1805	03.22	21 03 585 1420	03.74	21 04 416 1504	05.09
21 03 339 2301	03.55	21 03 415 7403	03.23	21 03 514 1805	03.25	21 03 585 1420	03.76	21 04 416 1505	05.07
		21 03 415 7404	03.21			21 03 585 1451	03.74	21 04 416 1505	05.09
21 03 341 1425	03.50	21 03 415 7404	03.23	21 03 515 4401	03.21	21 03 585 1451	03.76	21 04 416 3501	05.07
21 03 341 1505	03.56	21 03 415 7405	03.21	21 03 515 4401	03.24	21 03 585 1457	03.74	21 04 416 3501	05.09
21 03 341 1518	03.58	21 03 415 7405	03.23	21 03 515 4402	03.21	21 03 585 1457	03.76	21 04 416 3502	05.07
21 03 341 2425	03.51			21 03 515 4402	03.24	21 03 585 3401	03.75	21 04 416 3502	05.09
21 03 341 2505	03.57	21 03 449 4301	03.47	21 03 515 4403	03.21	21 03 585 3401	03.76	21 04 416 3503	05.07
21 03 341 2518	03.59	21 03 449 4301	03.49	21 03 515 4403	03.24	21 03 585 3403	03.75	21 04 416 3503	05.09
21 03 341 6401	03.62	21 03 449 4302	03.47	21 03 515 4404	03.21	21 03 585 3405	03.75	21 04 416 3504	05.07
		21 03 449 4302	03.49	21 03 515 4404	03.24	21 03 585 3405	03.76	21 04 416 3504	05.09
21 03 371 1400	03.86	21 03 449 4303	03.47	21 03 515 4405	03.21	21 03 585 3410	03.75	21 04 416 3505	05.07
21 03 371 1403	03.82	21 03 449 4303	03.49	21 03 515 4405	03.24	21 03 585 3410	03.76	21 04 416 3505	05.09
21 03 371 1420	03.84	21 03 449 4304	03.47	21 03 515 7401	03.21	21 03 585 3420	03.75		
21 03 371 2403	03.83	21 03 449 4304	03.49	21 03 515 7401	03.24	21 03 585 3420	03.76		
21 03 371 2415	03.87	21 03 449 4305	03.47	21 03 515 7402	03.21	21 03 585 3451	03.75	21 04 516 1402	05.08
		21 03 449 4305	03.49	21 03 515 7402	03.24	21 03 585 3451	03.76	21 04 516 2302	05.08
21 03 381 1418	03.89	21 03 449 6301	03.47	21 03 515 7403	03.21	21 03 585 3451	03.76	21 04 516 2501	05.07
21 03 381 1425	03.78	21 03 449 6301	03.49	21 03 515 7404	03.21	21 03 585 3457	03.75	21 04 516 2501	05.09
21 03 381 2400	03.84	21 03 449 6302	03.47	21 03 515 7404	03.24	21 03 585 3457	03.76	21 04 516 2502	05.07
21 03 381 2401	03.84	21 03 449 6302	03.49	21 03 515 7405	03.21	21 03 812 1405	03.16	21 04 516 2502	05.09
21 03 381 2418	03.90	21 03 449 6303	03.47	21 03 515 7405	03.24	21 03 812 1505	03.16	21 04 516 2503	05.07
21 03 381 2425	03.79	21 03 449 6303	03.49			21 03 812 2405	03.18	21 04 516 2503	05.09
21 03 381 2800	04.07	21 03 449 6304	03.49	21 03 549 1301	03.47	21 03 812 2505	03.18	21 04 516 2504	05.09
21 03 381 2801	04.12	21 03 449 6305	03.47	21 03 549 1301	03.48			21 04 516 2505	05.07
21 03 381 2802	04.09	21 03 449 6305	03.49	21 03 549 1302	03.47			21 04 516 2505	05.09
21 03 381 2803	04.09			21 03 549 1302	03.48	21 03 821 1505	03.16	21 04 516 4501	05.07
21 03 381 2804	04.10			21 03 549 1303	03.47			21 04 516 4501	05.07
21 03 381 2805	04.10	21 03 483 1801	04.06	21 03 549 1303	03.48	21 03 822 1425	03.28	21 04 516 4502	05.07
21 03 381 2806	04.11	21 03 483 1803	04.06	21 03 549 1304	03.47	21 03 822 1525	03.28	21 04 516 4502	05.09
21 03 381 2807	04.11	21 03 483 1805	04.06	21 03 549 1304	03.48	21 03 822 2425	03.29	21 04 516 4503	05.07
21 03 381 2809	04.10	21 03 483 1807	04.06	21 03 549 1305	03.47	21 03 822 2525	03.29	21 04 516 4503	05.09
21 03 381 4400	03.84	21 03 483 1810	04.06	21 03 549 1305	03.48	21 03 822 2535	07.04	21 04 516 4504	05.07
21 03 381 4401	03.84	21 03 483 5801	04.06	21 03 549 2301	03.47	21 03 822 3505	03.17	21 04 516 4504	05.09
21 03 381 4410	03.88	21 03 483 5802	04.06	21 03 549 2301	03.49	21 03 822 4505	03.19	21 04 516 4505	05.07
21 03 381 4411	03.88	21 03 483 5850	04.06	21 03 549 2302	03.47			21 04 516 4505	05.09
21 03 381 4412	03.88	21 03 483 5851	04.06	21 03 549 2302	03.49				
21 03 381 4413	03.88	21 03 483 5852	04.06	21 03 549 2303	03.47	21 03 841 1505	03.44		
21 03 381 4430	03.88			21 03 549 2303	03.49	21 03 841 1525	03.52		
21 03 381 4432	03.88	21 03 485 1401	03.74	21 03 549 2304	03.47	21 03 841 1535	07.05		
21 03 381 4800	04.07	21 03 485 1401	03.76	21 03 549 2304	03.49	21 03 841 2505	03.45	21 83 515 4401	03.21
21 03 381 4802	04.09	21 03 485 1403	03.74	21 03 549 2305	03.47	21 03 841 2525	03.53	21 83 515 4401	03.25
21 03 381 4804	04.10	21 03 485 1403	03.76	21 03 549 2305	03.49			21 83 515 4402	03.21
21 03 381 6401	03.85	21 03 485 1405	03.74	21 03 549 3301	03.47	21 03 881 1405	03.69	21 83 515 4402	03.25
21 03 381 6405	03.85	21 03 485 1405	03.76	21 03 549 3301	03.48	21 03 881 1805	04.05	21 83 515 4403	03.21
21 03 381 6410	03.87	21 03 485 1410	03.74	21 03 549 3302	03.47	21 03 881 5805	04.05	21 83 515 4403	03.25
21 03 381 6420	03.87	21 03 485 1410	03.76	21 03 549 3302	03.48			21 83 515 4404	03.21
21 03 381 6815	04.08	21 03 485 1420	03.74	21 03 549 3303	03.47			21 83 515 4404	03.25
		21 03 485 1420	03.76	21 03 549 3303	03.48	21 03 882 1405	03.68	21 83 515 4405	03.21
21 03 415 2401	03.21	21 03 485 1451	03.74	21 03 549 3304	03.47	21 03 882 1415	03.68	21 83 515 4405	03.25
21 03 415 2401	03.23	21 03 485 1451	03.76	21 03 549 3304	03.48	21 03 882 1425	03.80	21 83 515 7401	03.21
21 03 415 2402	03.21	21 03 485 1457	03.74	21 03 549 3305	03.47	21 03 882 1435	07.05	21 83 515 7401	03.25
21 03 415 2402	03.23	21 03 485 1457	03.76	21 03 549 3305	03.48	21 03 882 2405	03.70	21 83 515 7402	03.21
21 03 415 2403	03.21	21 03 485 3401	03.75	21 03 549 4301	03.47	21 03 882 2425	03.81	21 83 515 7402	03.25
21 03 415 2403	03.23	21 03 485 3401	03.76	21 03 549 4301	03.49	21 03 882 3405	03.69	21 83 515 7403	03.21
21 03 415 2404	03.21	21 03 485 3403	03.75	21 03 549 4302	03.47			21 83 515 7403	03.25
21 03 415 2404	03.23	21 03 485 3403	03.76	21 03 549 4302	03.49			21 83 515 7404	03.21
21 03 415 2405	03.21	21 03 485 3405	03.75	21 03 549 4303	03.47			21 83 515 7404	03.25
21 03 415 2405	03.23	21 03 485 3405	03.76	21 03 549 4303	03.49	21 04 116 1505	05.04	21 83 515 7405	03.21
21 03 415 5401	03.21	21 03 485 3410	03.75	21 03 549 4304	03.47	21 04 116 2505	05.05	21 83 515 7405	03.25

Be

Catalogue order information




Please send me further information:




Interface Connectors



Device Connectivity



Industrial
Connectors Han®



Connectors
DIN 41612



Coaxial and Metric
Connectors



Intelligent Network
Solutions



Application
brochure



TCA Connectors



High Speed
Backplanes

Sender:

Company: _____

Street: _____

Department: _____

Postcode/Town: _____

Name: _____

Country: _____

Prename: _____


Phone: _____

Function: _____

Fax: _____

Please send it by post or fax to your local HARTING representatives (see page addresses) or visit us under www.HARTING.com.

E-Mail: _____



Sales Network – worldwide



Afghanistan

see United Arab Emirates

Albania

see Eastern Europe

Argentina

Condelectric S.A.
Hipólito Yrigoyen 2591, 1640 - Martínez
Buenos Aires – Argentina
Phone +54 11 4836 1053
Fax +54 11 4836 1053
comercial@condelectric.com.ar

Armenia

see Eastern Europe

Australia

HARTING Pty Ltd
Suite 11 / 2 Enterprise Drive
Bundoora 3083, AUS-Victoria
Phone +61 3 9466 7088
Fax +61 3 9466 7099
au@HARTING.com
www.HARTING.com.au

Austria

HARTING Ges.m.b.H.
Deutschstraße 19, A-1230 Wien
Phone +431 6162121
Fax +431 6162121-21
at@HARTING.com
www.HARTING.at

Azerbaijan

see Eastern Europe

Bahrain

see United Arab Emirates

Belgium

HARTING N.V./S.A.
Z.3 Doornveld 23, B-1731 Zellik
Phone +32 2 466 0190
Fax +32 2 466 7855
be@HARTING.com
www.HARTING.be

Bosnia and Herzegovina

see Eastern Europe

Brazil

HARTING Ltda.
Rua Major Paladino 128 –
Prédio 11
CEP 05307-000 – São Paulo –
SP – Brasil
Phone +55 11 5035 0073
Fax +55 11 5034 4743
br@HARTING.com
www.HARTING.com.br

Brunei

see Singapore

Bulgaria

see Eastern Europe

Canada

HARTING Canada Inc.
8455 Trans-Canada Hwy., Suite 202
St. Laurent, QC, H4S1Z1, Canada
Phone 855-659-6653
Fax 855-659-6654
info.ca@HARTING.com
www.HARTING.ca

China

HARTING (Zhuhai)
Manufacturing Co., Ltd.
Shanghai Branch, Room 3501- 3503,
No. 1, Hong Qiao Road, Grand Gateway I
Xu Hui District, Shanghai 200030, China
Phone +86 21 6386 2200
Fax +86 21 6386 8636
cn@HARTING.com
www.HARTING.com.cn

Croatia

see Eastern Europe

Czech Republic

HARTING s.r.o.
Mlýnská 2, CZ-160 00 Praha 6
Phone +420 220 380 460
Fax +420 220 380 461
cz@HARTING.com
www.HARTING.cz

Denmark

HARTING ApS
Hjulmagervej 4a
DK - 7100 Vejle
Phone +45 70 25 00 32
Fax +45 75 80 64 99
dk@HARTING.com
www.HARTING.dk

Sales Network – worldwide



Eastern Europe

HARTING Eastern Europe GmbH
Bamberger Straße 7
D-01187 Dresden
Phone +49 351 4361 760
Fax +49 351 436 1770
Eastern.Europe@HARTING.com
www.HARTING.com

Egypt

see United Arab Emirates

Estonia

see Eastern Europe

Finland

HARTING Oy
Teknobulevardi 3-5
FI-01530 Vantaa
Phone +358 207 291 510
Fax +358 207 291 511
fi@HARTING.com
www.HARTING.fi

France

HARTING France
181 avenue des Nations, Paris Nord 2
BP 66058 Tremblay en France
F-95972 Roissy Charles de Gaulle Cédex
Phone +33 1 4938 3400
Fax +33 1 4863 2306
fr@HARTING.com
www.HARTING.fr

Germany

HARTING Deutschland GmbH & Co. KG
P.O. Box 2451, D-32381 Minden
Simeonscarré 1, D-32427 Minden
Phone +49 571 8896 0
Fax +49 571 8896 282
de@HARTING.com
www.HARTING.de

Georgia

see Eastern Europe

Great Britain

HARTING Ltd., Caswell Road
Brackmills Industrial Estate
GB-Northampton, NN4 7PW
Phone +44 1604 827 500
Fax +44 1604 706 777
gb@HARTING.com
www.HARTING.co.uk

Hong Kong

HARTING (HK) Limited
Regional Office Asia Pacific
3512 Metroplaza Tower 1
223 Hing Fong Road
Kwai Fong, N. T., Hong Kong
Phone +852 2423 7338
Fax +852 2480 4378
ap@HARTING.com
www.HARTING.com.hk

Hungary

HARTING Magyarország Kft.
Fehérvári út 89-95, H-1119 Budapest
Phone +36 1 205 34 64
Fax +36 1 205 34 65
hu@HARTING.com
www.HARTING.hu

India

HARTING India Pvt Ltd
7th Floor (West Wing), Central Square II
Unit No.B-19 Part, B 20&21
TVK Industrial Estate
Guindy, Chennai - 600032
Phone +91-44-43560415
+91-44-43456262
Fax +91-44-43560417
in@HARTING.com
http://www.HARTING.in

Indonesia

see Malaysia

Iran

see United Arab Emirates

Iraq

see United Arab Emirates

Israel

COMTEL
Israel Electronic Solutions Ltd.
Bet Hapamon, 20 Hataas st.
P.O.Box 66
Kefar-Saba 44425
Phone +972-9-7677240
Fax +972-9-7677243
sales@comtel.co.il
www.comtel.co.il

Italy

HARTING SpA
Via Dell' Industria 7
I-20090 Vimodrone (Milano)
Phone +39 02 250801
Fax +39 02 2650 597
it@HARTING.com
www.HARTING.it

Japan

HARTING K. K.
Yusen Shin-Yokohama 1 Chome Bldg., 2F
1-7-9, Shin-Yokohama, Kohoku
Yokohama 222-0033 Japan
Phone +81 45 476 3456
Fax +81 45 476 3466
jp@HARTING.com
www.HARTING.co.jp

Jemen

see United Arab Emirates

Jordan

see United Arab Emirates

Kazakhstan

see Eastern Europe

Kirghizia

see Eastern Europe

Korea (South)

HARTING Korea Limited
#308 Yatap Leaders Building
342-1, Yatap-dong, Bundang-gu
Sungnam-City, Kyunggi-do
463-828, Republic of Korea
Phone +82 31 781 4615
Fax +82 31 781 4616
kr@HARTING.com
www.HARTING.co.kr

Kosovo

see Eastern Europe

Kuwait

see United Arab Emirates

Latvia

see Eastern Europe

Lebanon

see United Arab Emirates

Lithuania

see Eastern Europe

Macedonia

see Eastern Europe

Malaysia (Office)

HARTING Singapore Pte Ltd
Malaysia Branch
11-02 Menara Amcorp
Jln. Persiaran Barat
46200 PJ, Sel. D. E., Malaysia
Phone +60 3 / 7955 6173
Fax +60 3 / 7955 5126
sg@HARTING.com

Montenegro

see Eastern Europe

Netherlands

HARTING B.V.
Larenweg 44
NL-5234 KA ,s-Hertogenbosch
Postbus 3526
NL-5203 DM ,s-Hertogenbosch
Phone +31 736 410 404
Fax +31 736 440 699
nl@HARTING.com
www.HARTINGbv.nl

New Zealand

see Australia

Norway

HARTING A/S
Østensjøveien 36, N-0667 Oslo
Phone +47 22 700 555
Fax +47 22 700 570
no@HARTING.com
www.HARTING.no

Oman

see United Arab Emirates

Pakistan

see United Arab Emirates

Philippines

see Malaysia

Sales Network – worldwide



Poland

HARTING Polska Sp. z o. o.
ul. Duńska 9
PL- 54-427 Wrocław
Phone +48 71 352 81 71
Fax +48 71 350 42 13
pl@HARTING.com
www.HARTING.pl

Portugal

HARTING Iberia, S. A.
Avda. Josep Tarradellas 20-30 4º 6a
E-08029 Barcelona
Phone +351 219 673 177
Fax +351 219 678 457
es@HARTING.com
www.HARTING.es/pt

Qatar

see United Arab Emirates

Republic of Moldova

see Eastern Europe

Romania

HARTING Romania SCS
Europa Unita str. 21
550018-Sibiu, Romania
Phone +40 369-102 671
Fax +40 369-102 622
ro@HARTING.com
www.HARTING.com

Russia

HARTING ZAO
Maliy Sampsoniyevsky prospect 2A
194044 Saint Petersburg, Russia
Phone +7 812 327 6477
Fax +7 812 327 6478
ru@HARTING.com
www.HARTING.ru

Saudi Arabia

see United Arab Emirates

Serbia

see Eastern Europe

Singapore

HARTING Singapore Pte Ltd.
25 International Business Park
#04-108 German Centre
Singapore 609916
Phone +65 6225 5285
Fax +65 6225 9947
sg@HARTING.com
www.HARTING.sg

Slovakia

HARTING s.r.o.
Sales office Slovakia
J. Simora 5, SK - 940 52 Nové Zámky
Phone +421 356-493 993
Fax +421 356-402 114
sk@HARTING.com
www.HARTING.sk

Slovenia

see Eastern Europe

South Africa

HARTING South Africa (Pty) Ltd
Ground Floor, Twickenham Building
PO Box 67302
Johannesburg (Bryanston)
2021, South Africa
Phone +27 (0) 11 575 0017
Fax +27 (0) 11 576 6000
za@HARTING.com
www.HARTING.co.za

Spain

HARTING Iberia S.A.
Avda. Josep Tarradellas 20-30 4º 6a
E-08029 Barcelona
Phone +34 93 363 84 75
Fax +34 93 419 95 85
es@HARTING.com
www.HARTING.es

Sweden

HARTING AB
Gustavslundsvägen 141 B 4tr
S-167 51 Bromma
Phone +46 8 445 7171
Fax +46 8 445 7170
se@HARTING.com
www.HARTING.se

Switzerland

HARTING AG
Industriestrasse 26
CH-8604 Volketswil
Phone +41 44 908 20 60
Fax +41 44 908 20 69
ch@HARTING.com
www.HARTING.ch

Syria

see United Arab Emirates

Taiwan

HARTING Taiwan Ltd.
Room 1, 5/F
495 GuangFu South Road
RC-110 Taipei, Taiwan
Phone +886 2 2758 6177
Fax +886 2 2758 7177
tw@HARTING.com
www.HARTING.com.tw

Tajikistan

see Eastern Europe

Thailand

see Malaysia

Turkey

HARTING TURKEI Elektronik Ltd. Şti.
Barbaros Mah. Dereboyu Cad.
Fesleğen Sok.
Uphill Towers, A-1b Kat:8 D:45
34746 Ataşehir, İstanbul
Phone +90 216 688 81 00
Fax +90 216 688 81 01
tr@HARTING.com
www.HARTING.com.tr

Turkmenistan

see Eastern Europe

Ukraine

see Eastern Europe

United Arab Emirates

HARTING Middle East FZ-LLC
Knowledge Village, Block 2A, Office F72
P.O. Box 454372, Dubai
United Arab Emirates
Phone +971 4 453 9737
Fax +971 4 439 0339
uae@HARTING.com
www.HARTING.ae

USA

HARTING Inc. of North America
1370 Bowes Road
USA-Elgin, Illinois 60123
Phone +1 (877) 741-1500 (toll free)
Fax +1 (866) 278-0307 (Inside Sales)
us@HARTING.com
www.HARTING-USA.com

Uzbekistan

see Eastern Europe

Vietnam

see Singapore

Distributors – worldwide



Digi-Key Corporation:
www.digikey.com

Farnell:
www.farnell.com

FUTURE Electronics:
www.futureelectronics.com

Mouser Electronics:
www.mouser.com

RS Components:
www.rs-components.com

Other countries and general contact



HARTING Electronics GmbH
P.O. Box 1433
32328 Espelkamp - Germany
Phone +49 5772/47-97200
Fax +49 5772/47-777
electronics@HARTING.com



Pushing Performance

**HARTING.com –
the gateway to your
country website.**

www.HARTING.ae
www.HARTING.at
www.HARTING.com.au
www.HARTING.be
www.HARTING.com.br
www.HARTING.ca
www.HARTING.ch
www.HARTING.com.cn
www.HARTING.cz
www.HARTING.de
www.HARTING.dk
www.HARTING.es
www.HARTING-easterneurope.com
www.HARTING.fi
www.HARTING.fr
www.HARTING.co.uk
www.HARTING.com.hk
www.HARTING.hu
www.HARTING.co.in
www.HARTING.it
www.HARTING.co.jp
www.HARTING.co.kr
www.HARTINGbv.nl
www.HARTING.no
www.HARTING.pl
www.HARTING.pt
www.HARTING.ro
www.HARTING.ru
www.HARTING.se
www.HARTING.sg
www.HARTING.sk
www.HARTING.com.tr
www.HARTING.com.tw
www.HARTING-USA.com
www.HARTING.co.za